## 867 S TORX<sup>®</sup> bits for impact screwdrivers



Application: TORX® socket screws; for use with impact screwdriver 921

| Drive:  | 1/4" hexagonal |
|---------|----------------|
| Design: | Extra tough    |

|                      | 0     | ]; | ].                              |  |
|----------------------|-------|----|---------------------------------|--|
|                      |       | mm |                                 |  |
| 05 <b>018166</b> 001 | TX 15 | 70 | 2 <sup>3</sup> / <sub>4</sub> " |  |
| 05 <b>018167</b> 001 | TX 20 | 70 | 2 <sup>3</sup> / <sub>4</sub> " |  |
| 05 <b>018168</b> 001 | TX 25 | 70 | 2 <sup>3</sup> /4"              |  |
| 05 <b>018169</b> 001 | TX 30 | 70 | 2 <sup>3</sup> /4"              |  |
| 05 <b>018170</b> 001 | TX 40 | 70 | 2 <sup>3</sup> / <sub>4</sub> " |  |

## 851 S Phillips bits for impact screwdrivers





wera.de

|  | plication: |  |  |  |  |  |
|--|------------|--|--|--|--|--|
|  |            |  |  |  |  |  |
|  |            |  |  |  |  |  |
|  |            |  |  |  |  |  |

| Drive:  | 1/4" hexagonal |
|---------|----------------|
| Design: | Extra tough    |

|                      | $\mathbf{O}$ | ,  | l,                              |  |
|----------------------|--------------|----|---------------------------------|--|
|                      |              | mm |                                 |  |
| 05 <b>018160</b> 001 | PH 1         | 70 | 2 <sup>3</sup> / <sub>4</sub> " |  |
| 05 <b>018161</b> 001 | PH 2         | 70 | 2 <sup>3</sup> /4"              |  |
| 05 <b>018162</b> 001 | PH 3         | 70 | 2 <sup>3</sup> /4"              |  |

#### 855 S Pozidriv bits for impact screwdrivers



05**018165**001



Application: Suitable for Pozidriv screws; for use with impact screwdriver 921

| Drive:<br>Design:  |     | ¼4" hexagonal<br>Extra tough |    |                    |  |  |  |  |  |
|--------------------|-----|------------------------------|----|--------------------|--|--|--|--|--|
|                    |     | 0                            | ]; | ];                 |  |  |  |  |  |
|                    |     |                              | mm |                    |  |  |  |  |  |
| 05 <b>018163</b> 0 | 001 | PZ 1                         | 70 | 2 <sup>3</sup> /4" |  |  |  |  |  |
| 05 <b>018164</b> 0 | 001 | PZ 2                         | 70 | 2 <sup>3</sup> /4" |  |  |  |  |  |

70

2 <sup>3</sup>/<sub>4</sub>"

PZ 3

# **Combination tool**



The 921 impact screwdriver combines the advantages of interchangeable blade sets, chiseldrivers and manual impact wrenches.

# Handle/interchangeable blade system



The robust bit mounting is suitable for bits with  $1/4^{"}$  external hexagon drive as per DIN ISO 1173-C 6.3 and E 6.3. The interchangeable blade system means low weight, reduced space requirement and high flexibility for the user.



# Impact wrench function can be switched on and off



### The manual impact wrench function can be switched on if required to loosen even stubborn screw connections.



# Loosening moment



With the impact wrench function switched on, the hammer blow impulse is converted into a rotary movement with a loosening moment of up to 25 Nm. Power transmission without loss via a pound-thru blade.