



<b>Product / Process Change Notification (PCN)</b>	
<input checked="" type="checkbox"/> Major change <input type="checkbox"/> Minor change	
<b>PCN #:</b> PCN_IndSL2_20221003 <b>Affected Series:</b> WE-SL2; 744xxx(S) <b>PCN Date:</b> September 03, 2022 <b>Effective Date:</b> October 03, 2022	<b>Change Category:</b> <input type="checkbox"/> Equipment / Location <input type="checkbox"/> General Data <input checked="" type="checkbox"/> Material <input type="checkbox"/> Process <input type="checkbox"/> Product Design <input type="checkbox"/> Shipping / Packaging <input type="checkbox"/> Supplier <input type="checkbox"/> Software
<b>Contact:</b> Product Management <b>Phone:</b> +49 (0) 7942 - 945 5001 <b>Fax:</b> +49 (0) 7942 - 945 5179 <b>E-Mail:</b> pcn.eisos@we-online.com	<b>Data Sheet Change:</b> <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <b>Attachment:</b> <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
<b>Description and purpose of change:</b> <p>In order to enhance the product reliability, Würth Elektronik will change the wire supplier.</p> <p>Products with date code 2022-11-14 or later, will be affected by this change.</p> <p>This change will be implemented gradually and it can be identified in the last number of the Lot Number (LN).</p> <p>There will be no change in form, fit, function, quality of the product.</p>	
<b>Detail of Change:</b> Affected part numbers are: <ul style="list-style-type: none"> <li>- 744221</li> <li>- 744222</li> <li>- 744223</li> <li>- 744224</li> <li>- 744225</li> <li>- 744226</li> <li>- 744228</li> <li>- 744225S</li> </ul>	



- 744226S
- S19100046
- S20100183

**Before:**

**Wire PROSPERITY 2-UEW-H**

**LN: 226xxxxxxxxxxx0**

**LN: 226xxxxxxxxxxx1**

**After:**

**Wire ELEKTRISOLA P180-G2**

**LN: 226xxxxxxxxxxx3**

**LN: 226xxxxxxxxxxx4**

**Reliability / Qualification Summary:**

Product approval is according to the specification criteria and is internally released by the Product Management Department.

**The following items are part of the internal release process:**

- Biased Humidity (MIL-STD-202-103)
- Moisture Resistance (MIL-STD-202-106)
- Operational Life (MIL-PRF-27)
- Resistance to soldering heat (J-STD-020)
- ESD (IO/DIS 10605)
- Board Flex (AEC-Q200-005)
- Terminal Strength (AEC-Q200-006)