



## 13-4 GENERAL NITRILE

- (EN) VERY HIGH CUT - OILY - DURABLE  
 (DE) SEHR HOHER SCHNITTSCHUTZ - ÖLIG - LANGLEBIG  
 (SE) VÄLDIGT HÖGT SKÄRSKYDD - OLJIG - SLITSTARK  
 (NL) ZEER HOGE SNIJBESTENDIGHEID - OLIEACHTIG - DUURZAAM  
 (FI) ERITTÄIN TÄRKEÄÄ - ÖLJYMÄINEN - KESTÄVÄ  
 (NO) SVÆRT HØYT KUTT BESKYTTELSESNIVÅ - OLJETE - SLITESTERK  
 (DK) MEGET HØJ SKÆRBESKYTTELSE - OLIE - HOLDBAR  
 (FR) TRÈS HAUTE PROTECTION ANTI COUPE - HUILEUX - DURABLE  
 (IT) MOLTO ALTO PROTEZIONE DAL TAGLIO - OLEOSO - DUREVOLE  
 (ES) CORTE MUY ALTO - ACEITOSO - DURADERO  
 (PL) BARDZO WYSOKA ODPRONOŚĆ NA PRZECIĘCIE - OLEJ - TRWAŁOŚĆ  
 (RO) NIVEL ANTITAIERE FOARTE RIDICAT - ULEI - DURABIL  
 (AF) BAIE HOE SNY - OLIERIGE - DURSAAM  
 (SL) ZELO VISOKA ODPORNOST NA REZANJE - OLJNATO - VZDRŽLJIVO  
 (CZ) VELMI VYSOKÁ ŘEZNOST - MASTNÝ - ODOLNÝ

EN388:2016



4542F

- A: ABRASION (1-4)  
 B: CUT (1-5)  
 C: TEAR (1-4)  
 D: PUNCTURE (1-4)  
 F: ISO CUT (A-F)  
 P: IMPACT PROTECTION



CE  
 CAT II

The glove should only be used in accordance with the pictograms printed on the glove. Make sure your mechanical requirements are fulfilled within the pictogram result. Do not use in close proximity to rotating machinery.

Store the glove in its original packing in dark, cool and dry place.  
 Inspect glove before use. Wash in 30 degrees with regular detergent.  
 Gloves are not tested after washing. Use gloves within 3 years from purchase.

Glove is according to REGULATION (EU) 2016/425.  
 Glove complies with EN388:2016 and EN420:2003+A1:2009.



Produced by: Y.Berger&Co AB, Ingela Gathenhielms Gata 3,  
 SE 421 30 Västra Frölunda, Sweden.

For a copy of CE declaration or other details contact us through below:  
 Phone: +46 31 75 10 850, Email: eureka@berger.se, Website: www.eurekasafety.se  
 App: Eureka Safety Gloves

ART.NO: 13-4GNI

6 pairs / wrap - 60 pairs / carton



CUT RESISTANT - SCHNITTSCHUTZ