

product type designation

IWLAN panel feedthrough N-Connect/SMA Female/Female

N-Connect/SMA female/female panel feedthrough; cabinet bushing, 2.4 GHz and 5 GHz for wall thickness max. 5.5 mm.



electrical data	
number of electrical connections	2
type of electrical connection	N-Connect female/SMA female
transmission frequency	0 ... 6 GHz
impedance	50 Ω
ambient conditions	
ambient temperature	
• during operation	-40 ... +70 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
protection class IP	IP67
design, dimensions and weights	
width	25.4 mm
height	25.4 mm
length	31.3 mm
net weight	35 g
standards, specifications, approvals	
certificate of suitability	
• RoHS conformity	Yes
further information / internet-Links	
Internet-Link	
• to website: TIA Selection Tool	http://www.siemens.com/tia-selection-tool
• to web page: selection aid TIA Selection Tool	http://www.siemens.com/snst
• to the website: IWLAN	http://www.siemens.com/iwlan
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Selection guide for cables and connectors	https://sie.ag/2QdlxcP
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx-Download-Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
last modified:	5/20/2021 