

MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918

Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com

www.mikroe.com

AD-SWIO click





PID: MIKROE-4081

AD-SWIO Click is a guad-channel software configurable input/output solution based on AD74412R. The AD74412R is a quad-channel software configurable input/output integrated circuit for building and process control applications. The device provides a fully integrated single chip solution for input and output operation. The AD-SWIO Click contains four 13-bit DACs, one per chanal, and 16-bit Σ - Δ ADC. These options give a lot of flexibility in choosing functionality for analog output, analog input, digital input, resistance temperature detector (RTD), and thermocouple measurements integrated into a single chip solution with a serial peripheral interface (SPI).

The AD-SWIO Click is supported by a mikroSDK compliant library, which includes functions that simplify software development. This Click board $^{\mathsf{m}}$ comes as a fully tested product, ready to be used on a system equipped with the mikroBUS[™] socket.

Mikroe produces entire development toolchains for all major microcontroller architectures. Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.







MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918
Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com

www.mikroe.com

Specifications

Туре	SWIO,ADC-DAC
Applications	Applications Its a perfect choice for Process control, Factory automation, Motor drives, Building control systems.
On-board modules	AD74412R a quad-channel SWIO and ADP1613 step-up dc-to-dc switching converter all from Analog Devices
Key Features	Optimized for 16-bit ADC (Analog-to-Digital Converter) and 13-bit DAC (Digital-to-Analog Converter).
Interface	GPIO,SPI
Compatibility	mikroBUS
Click board size	L (57.15 x 25.4 mm)
Input Voltage	3.3V,5V

Resources

mikroBUS™ Standard specification

LibStock: mikroSDK

Click board catalog

Click boards™ Standard Page


Downloads

AD-SWIO click example on Libstock

AD-SWIO click schematic

AD-SWIO click 2D and 3D files

AD74412R datasheet







health and safety management system.