KONTAKT CHEMIE ®

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

SCREEN 99

of the mixture

Registration number

UFI: 2T4X-7841-700V-MK0J

Synonyms None.

Product code BDS002581AE Issue date 20-May-2021

Version number 2.0

Revision date 24-March-2022 Supersedes date 20-May-2021

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaners - Precision

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company name CRC Industries Europe by

Address Touwslagerstraat 1

9240 Zele Belgium

Telephone +32(0)52/45.60.11

hse@crcind.com www.crcind.com

Company name CRC Industries UK Ltd.

Address Wylds Road

Castlefield Industrial Estate
TA6 4DD Bridgwater Somerset

United Kingdom

 Telephone
 +44 1278 727200

 Fax
 +44 1278 425644

 E-mail
 hse.uk@crcind.com

 Website
 www.crcind.com

1.4. Emergency telephone

Tel.:(+44)(0)1278 72 7200 (office hours: 9-17h CET)

number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Aerosols Category 1 H222 - Extremely flammable

aerosol.

H229 - Pressurized container: May

burst if heated.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Hazard pictograms

Trazard pictograms

Signal word Danger

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurized container: May burst if heated.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

Response Not assigned.

Storage

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information EUH208 - Contains 1,2-benzisothiazol-3(2H)-one;1,2-benzisothiazolin-3-one. May produce an

allergic reaction.

Regulation (EC) No 648/2004 on detergents:

aliphatic hydrocarbons 5-15%

perfumes: d-limonene

benzisothiazolinone, benzoic acid

2.3. Other hazards

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or

Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

Mixture

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Propan-2-ol; Isopropyl alcohol; Isopropanol	5 - 10	67-63-0 200-661-7	01-2119457558-25	603-117-00-0	#
Classification:	Flam. Liq.	2;H225, Eye Irrit. 2;H	319, STOT SE 3;H336		
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane	1 - 5	EC921-024-6 921-024-6	01-2119475514-35	-	
		2;H225, Skin Irrit. 2;F quatic Chronic 2;H41	l315, STOT SE 3;H336, As _l 1	о. Тох.	
1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER	<5	107-98-2 203-539-1	01-2119457435-35	603-064-00-3	#
Classification:	Flam. Liq.	3;H226, STOT SE 3;	H336		
1,2-benzisothiazol-3(2H)-one;1,2-ben zisothiazolin-3-one	<0.05	2634-33-5 220-120-9	01-2120761540-60	613-088-00-6	
	2;H315, E	, ,	2;H330, Acute Tox. 4;H332, Sens. 1;H317, Aquatic Acu		

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

ATE: Acute toxicity estimate.

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth. Ingestion

4.2. Most important symptoms and effects, both acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Extremely flammable aerosol.

5.1. Extinguishing media

Suitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters

Special fire fighting procedures

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. In the

event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

For emergency responders

Keep unnecessary personnel away. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. This product is miscible in water. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)

7.3. Specific end use(s) Not available.

Material name: SCREEN 99 - Kontakt chemie - Europe SDS GREAT BRITAIN BDS002581AE Version #: 2.0 Revision date: 24-March-2022 Issue date: 20-May-2021

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

UK. EH40 Workplace Exposure Limits (WELs
--

Components	Type	Value	
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	560 mg/m3	
		150 ppm	
	TWA	375 mg/m3	
		100 ppm	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1250 mg/m3	
		500 ppm	
	TWA	999 mg/m3	
		400 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Recommended monitoring

procedures

Follow standard monitoring procedures.

Derived no effect levels (DNELs)

General Population

Components	Value	Assessment factor	Notes
1,2-benzisothiazol-3(2H)-one;1,2-benzisothia:	zolin-3-one (CAS 2634-33-5)		
Long-term, Systemic, Dermal Long-term, Systemic, Inhalation	0.345 mg/kg bw/day 1.2 mg/m3	200 50	Repeated dose toxicity Repeated dose toxicity
1-METHOXY-2-PROPANOL; MONOPROPYL	ENE GLYCOL METHYL ETH	IER (CAS 107-98-2)	
Long-term, Systemic, Dermal Long-term, Systemic, Inhalation Long-term, Systemic, Oral	78 mg/kg bw/day 43.9 mg/m3 33 mg/kg bw/day	16.8 28	Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity
Hydrocarbons, C6-C7, n-alkanes, isoalkanes,	cyclics,< 5% n-hexane (CAS E	EC921-024-6)	
Long-term, Systemic, Dermal Long-term, Systemic, Inhalation Long-term, Systemic, Oral	699 mg/kg bw/day 608 mg/m3 699 mg/kg bw/day	·	
Propan-2-ol; Isopropyl alcohol; Isopropanol (C	CAS 67-63-0)		
Long-term, Systemic, Dermal Long-term, Systemic, Inhalation Long-term, Systemic, Oral	319 mg/kg bw/day 89 mg/m3 26 mg/kg bw/day	2 2 2	Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity
<u>Workers</u>			
Components	Value	Assessment factor	Notes
1,2-benzisothiazol-3(2H)-one;1,2-benzisothia	zolin-3-one (CAS 2634-33-5)		
Long-term, Systemic, Dermal Long-term, Systemic, Inhalation	0.966 mg/kg bw/day 6.81 mg/m3	100 25	Repeated dose toxicity Repeated dose toxicity
1-METHOXY-2-PROPANOL; MONOPROPYL	ENE GLYCOL METHYL ETH	IER (CAS 107-98-2)	
Long-term, Systemic, Dermal Long-term, Systemic, Inhalation Short-term, Local, Inhalation Short-term, Systemic, Inhalation	183 mg/kg bw/day 369 mg/m3 553.5 mg/m3 553.5 mg/m3	10.08	Repeated dose toxicity Repeated dose toxicity Neurotoxicity Neurotoxicity
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,	cyclics,< 5% n-hexane (CAS E	EC921-024-6)	
Long-term, Systemic, Dermal Long-term, Systemic, Inhalation	773 mg/kg bw/day 2035 mg/m3		
Propan-2-ol; Isopropyl alcohol; Isopropanol (C	CAS 67-63-0)		
Long-term, Systemic, Dermal Long-term, Systemic, Inhalation	888 mg/kg bw/day 500 mg/m3	1 1	
dicted no effect concentrations (PNECs)			
Components	Value	Assessment factor	Notes

100

Material name: SCREEN 99 - Kontakt chemie - Europe

Freshwater

SDS GREAT BRITAIN

BDS002581AE Version #: 2.0 Revision date: 24-March-2022 Issue date: 20-May-2021

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)

10 mg/l

Sediment (freshwater) 52.3 mg/kg 4.59 mg/kg Soil STP

100 mg/l

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0) Freshwater 140.9 mg/l

Secondary poisoning 160 mg/kg 30 Oral

Sediment (freshwater) 552 mg/kg Soil 28 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

10

Individual protection measures, such as personal protective equipment

Use personal protective equipment as required. Personal protection equipment should be chosen **General information**

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection Wear safety glasses with side shields (or goggles). Use eye protection conforming to EN 166.

Skin protection

When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough - Hand protection

time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Suitable gloves can be recommended by the glove supplier. Full contact: Glove material: nitrile. Use gloves with

breakthrough time of 480 minutes. Minimum glove thickness 0.38 mm.

Not available. - Other

In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with Respiratory protection

organic vapour cartridge. (Filter type AX)

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

When using do not smoke. Always observe good personal hygiene measures, such as washing Hygiene measures

after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

Environmental exposure

controls

Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Liquid. Physical state **Form** Aerosol. Colour Colourless. Citrus. Odour

Odour threshold Not available.

8 - 9.5 pН

Melting point/freezing point -95 °C (-139 °F) estimated 61 °C (141.8 °F) estimated Initial boiling point and boiling

range

Flash point < 0 °C (< 32.0 °F)

Not available. **Evaporation rate** Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

2.5 % estimated

(%)

Flammability limit - upper 12 % estimated

(%)

999.9 hPa estimated Vapour pressure

Not available. Vapour density 1 g/cm3 Relative density

Relative density temperature 20 °C (68 °F)

Solubility(ies)

Solubility (water)Soluble in waterAuto-ignition temperature> 200 °C (> 392 °F)Decomposition temperatureNot available.

Viscosity
Not available.

Explosive properties
Not explosive.

Not explosive.

Not oxidising.

9.2. Other information

Aerosol spray enclosed space

Time equivalent > 480 s/m³
Aerosol spray ignition < 15 cm

distance

Heat of combustion (NFPA

30B)

2.53 kJ/g estimated

VOC 210 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Avoid high temperatures.

10.5. Incompatible materials Strong oxidising agents. Chlorine. Isocyanates.

10.6. Hazardous Carbon oxides.

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation May cause allergy or asthma symptoms or breathing difficulties if inhaled. Prolonged inhalation

may be harmful.

Eye contact Causes serious eye irritation.

Skin contact May cause an allergic skin reaction.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision.

11.1. Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met. Classification based on calculation

method.

Components Species Test Results

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)

<u>Acute</u>

Dermal

LD50 Rabbit 13 g/kg

Inhalation

LC50 Rat 54.6 mg/l, 4 Hours

Oral

LD50 Rat 5.71 g/kg

Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane

Acute Dermal

LD50 Rat 2920 mg/kg bw/day, 24 h

Inhalation

LC50 Rat 25200 mg/m³, 4 h

Components Species Test Results

Oral

LD50 Rat 5840 mg/kg bw/day

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

Acute

Inhalation

LC50 Rat > 25000 mg/m3, 6 h

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory sensitisation

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Specific target organ toxicity -

single exposure

Based on available data, the classification criteria are not met.

Specific target organ toxicity -

repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard Not likely, due to the form of the product.

Mixture versus substance

information

Not available.

Other information May cause allergic respiratory and skin reactions.

SECTION 12: Ecological information

12.1. Toxicity Harmful to aquatic life with long lasting effects.

Components Species Test Results

1,2-benzisothiazol-3(2H)-one;1,2-benzisothiazolin-3-one (CAS 2634-33-5)

Aquatic

Acute

Crustacea LC50 Harpacticoid copepod (Nitocra spinipes) >= 21 - <= 30 mg/l, 96 hours
Fish LC50 Bleak (Alburnus alburnus) >= 8 - <= 13 mg/l, 96 hours

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)

Aquatic

Acute

 Algae
 EC50
 Algae
 > 1000 mg/l, 72 h

 Crustacea
 EC50
 Daphnia
 > 1000 mg/l, 48 h

 Fish
 LC50
 Oncorhynchus mykiss
 > 1000 mg/l, 96 h

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Aquatic

Acute

 Crustacea
 EC50
 Daphnia
 3 mg/l, 48 h

 Fish
 LC50
 Fish
 11.4 mg/l, 96 h

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

Aquatic

Acute

Crustacea LC50 Brine shrimp (Artemia salina) > 10000 mg/l, 24 hours
Fish LC50 Bluegill (Lepomis macrochirus) > 1400 mg/l, 96 hours

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Partition coefficient

n-octanol/water (log Kow)

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL -0.49

METHYL ETHER

Propan-2-ol; Isopropyl alcohol; Isopropanol 0.05

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB

assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII.

12.6. Other adverse effectsThe product contains volatile organic compounds which have a photochemical ozone creation

potential.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

EU waste codeThe Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Special precautions Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number UN1950

14.2. UN proper shipping

AEROSOLS, flammable

name

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Hazard No. (ADR) Not available.

Tunnel restriction code D

14.4. Packing group Not available.

14.5. Environmental hazards No

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

RID

14.1. UN number UN1950

14.2. UN proper shipping AEROSOLS, flammable

name

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

14.4. Packing group Not available.

14.5. Environmental hazards No

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

ADN

14.1. UN number UN1950

14.2. UN proper shipping AEROSOLS, flammable

name

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

14.4. Packing group Not available.

Material name: SCREEN 99 - Kontakt chemie - Europe
BDS002581AE Version #: 2.0 Revision date: 24-March-2022 Issue date: 20-May-2021

14.5. Environmental hazards No

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

IATA

14.1. UN number UN1950 **14.2. UN proper shipping** AEROSOLS

name

14.3. Transport hazard class(es)
Class 2.1
Subsidiary risk -

14.4. Packing group Not applicable

14.5. Environmental hazards No

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

IMDG

14.1. UN number UN1950 **14.2. UN proper shipping** AEROSOLS

name

14.3. Transport hazard class(es)
Class 2.1
Subsidiary risk -

14.4. Packing group Not applicable

14.5. Environmental hazards

Marine pollutant

F-D, S-U

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

14.7. Transport in bulk according to Annex II of

MARPOL 73/78 and the IBC

Code

ADN; ADR; IATA; IMDG; RID



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Retained direct EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not established.

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

1,2-benzisothiazol-3(2H)-one;1,2-benzisothiazolin-3-one (CAS 2634-33-5)

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

15.2. Chemical safety

No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).

ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).

CAS: Chemical Abstract Service.

Ceiling: Short Term Exposure Limit Ceiling value.

CEN: European Committee for Standardization.

CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.

GWP: Global Warming Potential.

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals).

RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer).

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit.

TLV: Threshold Limit Value.

TWA: Time Weighted Average.

VLE: Exposure Limit Value.

VME: Exposure Average Value.

VOC: Volatile organic compounds.

vPvB: Very persistent and very bioaccumulative.

STEL: Short-term Exposure Limit.

References

Information on evaluation method leading to the classification of mixture

Full text of any H-statements not written out in full under Sections 2 to 15 Not available.

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

BDS002581AE Version #: 2.0 Revision date: 24-March-2022 Issue date: 20-May-2021

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Follow training instructions when handling this material.

evision information

This document has undergone significant changes and should be reviewed in its entirety.

Revision information Training information Disclaimer

CRC Industries Europe bvba cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.