

CHARACTERISSTICS

MATERIALS

SHELL: BRASS

SHELL PLATING: NICKEL

NUT: BRASS

NUT PLATING: NICKEL

LATCH SLEEVE: BRASS

LATCH SLEEVE PLATING: NICKEL CONTACTS: COPPER ALLOY

CONTACT PLATING: 7µ" GOLD PLATED OVER 196µ" NICKEL MIN. INSULATOR: PPS (HIGH TEMPERATURE)

MECHANICAL

DURABILITY: 5000 CYCLES

OPERATING TEMP. RANGE: -40°C~+200°C


PROCESS TEMPERATURE: 260°C FOR 5 SECONDS

MAX. TORQUE VALUE: 2.5 Nm [22.1 IN/lbs]

SHIELDING: 75dB @ 10MHz

40dB @ 1GHz

IP RATING: 50



PANEL CUTOUT

TOLERANCE = +0.10, -0.0[+0.004, -0.00]

0

CHART A





2 POSITION 22 AWG MAX. 10 AMP MAX. PIN Ø = 0.90 [0.035]

CONTACT RESISTANCE = $6 \text{ m}\Omega$ TEST VOLTAGE = 1300V WORKING VOLTAGE = 430V



3 POSITION 22 AWG MAX. 8 AMP MAX. PIN Ø = 0.90 [0.035]

CONTACT RESISTANCE = 6 mQ TEST VOLTAGE = 1200V WORKING VOLTAGE = 400V



4 POSITION 22 AWG MAX. 7 AMP MAX. PIN Ø = 0.70 [0.028]

CONTACT RESISTANCE = 7.5 mΩ
TEST VOLTAGE = 850V WORKING VOLTAGE = 280V



5 POSITION 22 AWG MAX. 6.5 AMP MAX. PIN Ø = 0.70 [0.028]

CONTACT RESISTANCE = $7.5 \text{ m}\Omega$ TEST VOLTAGE = 850V WORKING VOLTAGE = 280V



6 POSITION 28 AWG MAX. 2.5 AMP MAX. PIN $\phi = 0.50 [0.020]$

 $\begin{array}{l} \text{CONTACT} \\ \text{RESISTANCE} = 10 \ m\Omega \end{array}$ TEST VOLTAGE = 850V WORKING VOLTAGE = 280V



7 POSITION 28 AWG MAX. 2.5 AMP MAX. PIN Ø = 0.50 [0.020]

CONTACT RESISTANCE = $10 \text{ m}\Omega$ TEST VOLTAGE = 800V WORKING VOLTAGE = 260V



9 POSITION 28 AWG MAX. 2 AMP MAX. PIN Ø = 0.50 [0.020]

CONTACT RESISTANCE = $10 \text{ m}\Omega$ TEST VOLTAGE = 600V WORKING VOLTAGE = 200V

ROHS COMPLIANT



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION



DRAWN: M. SIGMON	DATE: 02-03-16	SCALE: N.T.S.	SHEET	1	DF 1	REV:
CHECKED:	DATE:		DWG NC		0BYYY-103R00	1