



Revision: September 22, 2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Super Lube® Metal Protecant and Corrosion Inhibitor
- · Article number: No other identifiers
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Penetrating oil Lubricant

- · 1.3 Details of the supplier of the Safety Data Sheet
- · Manufacturer/Supplier:

Synco Chemical Corporation 24 DaVinci Dr., P.O. Box 405 Bohemia, NY 11706

Telephone: 631-567-5300 Email: info@super-lube.com

· 1.4 Emergency telephone number:

ChemTel

1-800-255-3924 (US/Canada), 1-813-248-0585 (International), 1-300-954-583 (Australia), 0-800-591-6042 (Brazil), 400-120-0751 (China), 000-800-100-4086 (India), 800-099-0731 (Mexico)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EU) No 2015/830

Classifications listed also are applicable to the OSHA GHS Hazard Communication Standard (29CFR1910.1200).



Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

(Contd. on page 2)

Revision: September 22, 2020

Trade name: Super Lube® Metal Protecant and Corrosion Inhibitor

(Contd. of page 1)

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labelled according to the Globally Harmonized System within the United States (GHS).

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



- · Signal word Danger
- · Hazard-determining components of labelling:

Distillates (petroleum), hydrotreated light

· Hazard statements

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

Do NOT induce vomiting. P331

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Hazard description:
- · WHMIS-symbols: Not hazardous under WHMIS.
- · NFPA ratings (scale 0 4)



Health = 0 Fire = 1

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0

REACTIVITY Reactivity = 0

· HMIS Long Term Health Hazard Substances

None of the ingredients are listed.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description**: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

Revision: September 22, 2020

Trade name: Super Lube® Metal Protecant and Corrosion Inhibitor

(Contd. of page 2)

· Dangerous components:

CAS: 64742-47-8 EINECS: 265-149-8 Index number: 649-422-00-2

Distillates (petroleum), hydrotreated light

>50%

🕸 Asp. Tox. 1, H304

Additional information:

For the listed ingredients, the identity and exact percentages are being withheld as a trade secret. For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Take affected persons out into the fresh air.

Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air.

Seek immediate medical advice.

Provide oxygen treatment if affected person has difficulty breathing.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation is experienced, consult a doctor.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting: call for medical help immediately.

A person vomiting while laying on their back should be turned onto their side.

· 4.2 Most important symptoms and effects, both acute and delayed

Headache

Breathing difficulty

Nausea

Coughing

Dizziness

Disorientation

· Hazards

Danger of pulmonary oedema.

Danger of pneumonia.

Danger of impaired breathing.

· 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

If swallowed or in case of vomiting, danger of entering the lungs.

Medical supervision for at least 48 hours.

If necessary oxygen respiration treatment.

(Contd. on page 4)

Revision: September 22, 2020

Trade name: Super Lube® Metal Protecant and Corrosion Inhibitor

(Contd. of page 3)

Later observation for pneumonia and pulmonary oedema.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Extinguishing powder. Do not use water.

Carbon dioxide

Foam

- · For safety reasons unsuitable extinguishing agents: Water
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information Eliminate all ignition sources if safe to do so.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol.

Remove persons from danger area.

Particular danger of slipping on leaked/spilled product.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders). Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

Dispose contaminated material as waste according to item 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Avoid splashes or spray in enclosed areas.

Prevent formation of aerosols.

(Contd. on page 5)

Revision: September 22, 2020

Trade name: Super Lube® Metal Protecant and Corrosion Inhibitor

(Contd. of page 4)

Use only in well ventilated areas.

- · Information about fire and explosion protection: Protect from heat.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles:

Provide ventilation for receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

Information about storage in one common storage facility:

Do not store together with oxidising and acidic materials.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Keep container tightly sealed.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

64742-47-8 Distillates (petroleum), hydrotreated light

EL (Canada) Long-term value: 200 mg/m³ Skin

- DNELs No further relevant information available.
- · PNECs No further relevant information available.
- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid close or long term contact with the skin.

Avoid contact with the eyes.

· Respiratory protection:

Not required under normal conditions of use.

Use suitable respiratory protective device in case of insufficient ventilation.

Use suitable respiratory protective device when aerosol or mist is formed.

For spills, respiratory protection may be advisable.

Protection of hands:



(Contd. on page 6)

Revision: September 22, 2020

Trade name: Super Lube® Metal Protecant and Corrosion Inhibitor

(Contd. of page 5)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR Nitrile rubber, NBR Neoprene gloves

Eye protection:



Safety glasses

- · Body protection: Protective work clothing
- · Limitation and supervision of exposure into the environment

No further relevant information available.

· Risk management measures

See Section 7 for additional information. No further relevant information available.

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- · General Information

· Appearance:

Form:
Colour:
Translucent
Odour:
Solvent-like
Odour threshold:
Not determined.

pH-value:
Not determined.

Change in condition

Melting point/Melting range: Not Determined.

Boiling point/Boiling range: 224 - 252 °C (435 - 486 °F)

· Flash point: >96 °C (>205 °F)

· Flammability (solid, gaseous): Not applicable.

(Contd. on page 7)

Revision: September 22, 2020

Trade name: Super Lube® Metal Protecant and Corrosion Inhibitor

· Auto/Self-ignition temperature: Not determined. (Contd. of page 6)

• **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not self-igniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· Explosion limits:

• **Density at 20 °C (68 °F):** <1,0 g/cm³ (<8,345 lbs/gal)

Relative density Not determined.

Vapour density at 20 °C (68 °F)
 Evaporation rate at 20 °C (68 °F)
 1 g/cm³ (> 8,345 lbs/gal)
 1 g/cm³ (< 8,345 lbs/gal)

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Solvent content:

VOC (California) <1%

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions

Reacts with strong acids.

Reacts with strong oxidising agents.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.

Used empty containers may contain product gases which form explosive mixtures with air.

Toxic fumes may be released if heated above the decomposition point.

10.4 Conditions to avoid

Keep away from heat and direct sunlight.

Store away from oxidising agents.

- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Hydrocarbons

Revision: September 22, 2020

Trade name: Super Lube® Metal Protecant and Corrosion Inhibitor

(Contd. of page 7)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:
- LD/LC50 values relevant for classification:

64742-47-8 Distillates (petroleum), hydrotreated light

Oral LD50 > 5000 mg/kg (rat)

- Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Slight irritant effect on eyes.
- · Additional toxicological information:

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent. The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

· Acute effects (acute toxicity, irritation and corrosivity):

May be fatal if swallowed and enters airways.

May be harmful if swallowed.

· Repeated dose toxicity:

Repeated exposure may cause skin dryness or cracking.

May cause damage to organs through prolonged or repeated exposure.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark:

Due to mechanical actions of the product (e.g. agglutinations) damages may occur.

The product is oxygen-consuming. The declared action may be partly caused by lack of oxygen.

- Additional ecological information:
- · General notes:

This statement was deduced from the properties of the single components.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

(Contd. on page 9)

Revision: September 22, 2020

Trade name: Super Lube® Metal Protecant and Corrosion Inhibitor

(Contd. of page 8)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Contact waste processors for recycling information.

Product is recyclable as a waste oil. Deliver unused and/or contaminated product to waste oil collectors. Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number

· DOT, ADR, ADN, IMDG, IATA Not Regulated

· 14.2 UN proper shipping name

· DOT, ADR, ADN, IMDG, IATA Not Regulated

· 14.3 Transport hazard class(es)

· DOT, ADR, ADN, IMDG, IATA

· Class Not Regulated

· 14.4 Packing group

· DOT, ADR, IMDG, IATA Not Regulated

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Not applicable.

· 14.7 Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· UN "Model Regulation":

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- ·SARA
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

(Contd. on page 10)

Revision: September 22, 2020

Trade name: Super Lube® Metal Protecant and Corrosion Inhibitor

(Contd. of page 9)

· Proposition 65 (California):

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

Carcinogenic Categories

· EPA (Environmental Protection Agency)

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

TLV (Threshold Limit Value established by ACGIH)

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· Canada

· Canadian Domestic Substances List (DSL)

All ingredients are listed.

· Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients are listed.

· Canadian Ingredient Disclosure list (limit 1%)

None of the ingredients are listed.

Other regulations, limitations and prohibitive regulations

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients are listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H304 May be fatal if swallowed and enters airways.

(Contd. on page 11)

Revision: September 22, 2020

Trade name: Super Lube® Metal Protecant and Corrosion Inhibitor

(Contd. of page 10)

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

· Sources

SDS created by Environmental Protection Department