

Product characteristics

Electronic pressure sensor

e1 compliant

Process connection: 1/4" NPT A / M5 I

Analogue output

Measuring range: 0...3000 psi

Application

Application

Type of pressure: relative pressure
Liquids and gases

Use in gases at pressures > 363 psi (25 bar) only after contacting the manufacturer ifm

Pressure rating	[psi]	5800
Bursting pressure min.	[psi]	12300
Medium temperature	[°C]	-25...90

Electrical data

Electrical design

DC

Operating voltage	[V]	16...32 DC
Current consumption	[mA]	< 18
Insulation resistance	[MΩ]	> 100 (500 V DC)

Protection class

III

Reverse polarity protection		yes
-----------------------------	--	-----

Outputs

Output		Analogue output
Output function		0...10 V analogue

Overload protection

yes

Analogue output

0...10 V

Max. load	[Ω]	min. 2000
-----------	-----	-----------

Measuring / setting range

Measuring range	[psi]	0...3000
-----------------	-------	----------

Accuracy / deviations

Accuracy / deviations

(in % of the span)

Characteristics deviation *)		< ± 0.35 (BFSL) / < ± 0.75 (LS)
------------------------------	--	---------------------------------

Repeatability **)		< 0.15
-------------------	--	--------

Long-term stability ***)		< ± 0.05
--------------------------	--	----------


Temperature coefficients (TEMPCO) in the temperature range 0...80° C (in % of the span per 10 K)

Greatest TEMPCO of the zero point		0.2
-----------------------------------	--	-----

Greatest TEMPCO of the span		0.3
-----------------------------	--	-----

Reaction times

PX9111 - Electronic pressure sensor - eclass: 27201302 / 27-20-13-02

Step response time analogue output	[ms]	3
Environment		
Ambient temperature	[°C]	-25...80
Storage temperature	[°C]	-40...100
Protection		IP 68 / IP 69K
Tests / approvals		
EMC		EN 61000-4-2 ESD: 4 kV CD / 8 kV AD EN 61000-4-3 HF radiated: 30 V/m EN 61000-4-4 Burst: 2 kV EN 61000-4-6 HF conducted: 10 V according to the automotive radiation of interference directive 2004/104/EC / CISPR25 according to the automotive noise immunity directive 2004/104/EC / ISO 11452-2 HF radiated 100 V/m pulse resistance according to ISO7637-2 / severity level 3
Shock resistance		DIN IEC 68-2-27: 50 g (11 ms)
Vibration resistance		DIN IEC 68-2-6: 20 g (10...2000 Hz)
Mechanical data		
Process connection		1/4" NPT A / M5 I
Materials (wetted parts)		stainless steel (303S22); ceramics; FPM (Viton)
Housing materials		stainless steel 316L / 1.4404; FPM (Viton); PA; EPDM/X (Santoprene)
Min. pressure cycles		100 million
Weight	[kg]	0.215
Electrical connection		
Connection		M12 connector; Gold-plated contacts
Wiring		
2 1 3 4		
Remarks		
Remarks		*) BFSL = Best Fit Straight Line / LS = Limit Value Setting **) with temperature fluctuations < 10 K ***) in % of value of measuring range / 6 months
Pack quantity	[piece]	1

ifm electronic gmbh • Friedrichstraße 1 • 45128 Essen — We reserve the right to make technical alterations without prior notice. — GB — PX9111 — 22.11.2012