



### Model Number

**LHR 00-0,8-1,0-14M3**

Glass fiber optic - diffuse with silicon covering

Threading M3

### Features

- Chemical-resistant
- Thread M3
- High temperature rated to 180 °C
- High flexible

### Series

#### Fiber optic amplifiers

Device series SU18 ; SU18/35 ; SU19

### Description

#### Attention:

Fibre optics must not be twisted or kinked. Excessive tensile loads will lead to destruction.



### Accessories

#### OMH-LL-M3

Mounting bracket

### Technical data

#### General specifications

Sensor range		SU18: 40 mm SU18/35: 195 mm SU19: 40 mm
Fiber optic length	l	1000 mm
Fiber optic diameter	d	3 mm
Adapter form		00
End piece		thread
Bending radius		5 mm static
Fiber bundle diameter		0.8 mm
Fiber configuration	Fv	optical separated
Angle of divergence		68 °

#### Ambient conditions

Ambient temperature		-20 ... 85 °C (-4 ... 185 °F) [Adapter] -40 ... 180 °C (-40 ... 356 °F) [End head and Covering]
---------------------	--	--

#### Mechanical specifications

Material		
Optical face		glass
Sheathing		silicon
Core		Glass fiber
End piece		Stainless steel 1.4305 / AISI 303
Adapter		Stainless steel
Extraction force		50 N

### Dimensions

