


Mini slide DGSL-8-50-PA

Part number: 543930

FESTO



Data sheet

| Feature | Value |
|--|--|
| Stroke | 50 mm |
| Adjustable end-position range/front length | 35.5 mm |
| Adjustable end-position range/rear length | 18.5 mm |
| Piston diameter | 10 mm |
| Type code | DGSL |
| Drive unit operating mode | Yoke |
| Cushioning | Elastic cushioning rings/pads at both ends |
| Mounting position | Any |
| Guide | Ball bearing cage guide |
| Design | Yoke Slide Piston rod Piston |
| Position sensing | For proximity sensor |
| Symbol | 00991263 |
| Operating pressure | 1.5 bar ... 8 bar |
| Max. speed | 0.8 m/s |
| Repetition accuracy | 0.3 mm |
| Mode of operation | Double-acting |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC) | 0 - No corrosion stress |
| Ambient temperature | 0 °C ... 60 °C |
| Impact energy in the end positions | 0.08 J |
| Cushioning length | 1.5 mm |
| Max. force F _y | 962 N |
| Max. force F _z | 962 N |
| Max. torque M _x | 10 Nm |
| Max. torque M _y | 8 Nm |
| Max. torque M _z | 8 Nm |
| Theoretical force at 6 bar, retracting | 40 N |
| Theoretical force at 6 bar, advancing | 47 N |
| Moving mass | 152 g |
| Product weight | 382 g |
| Alternative connections | See product drawing |
| Type of mounting | With through-hole |

| Feature | Value |
|----------------------|---|
| Pneumatic connection | M3 |
| Note on materials | Free of copper and PTFE RoHS-compliant |
| Cover material | Wrought aluminum alloy |
| Seals material | HNBR |
| Housing material | Wrought aluminum alloy |
| Piston rod material | High-alloy stainless steel |