



Part Number : [192760006](#)

Product Description : Quixon Quick Disconnect, InsulKrimp Style, Female, Fully Insulated Blue, 14-16 AWG, Mylar Tap

Series Number : 19276

Status : Active

Product Category : Quick Disconnects

Engineering Number : BB-2206T-LIF



Documents & Resources

Drawings

[Drawing 192760006_sd.pdf](#)

3D Models and Design Files

[3D Model 192760006_stp.zip](#)

Specifications


[Product Specification PS-19902-011-001.pdf](#)

[Product Specification PS-19902-012-001.pdf](#)

[Product Specification PS-19902-015-001.pdf](#)

Product Environment Compliance

Compliance

| | |
|--------------------|---|
| GADSL/IMDS | Not Relevant |
| China RoHS |  |
| EU ELV | Not Relevant |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2023)3788-DC (14 Jun 2023) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS

- REACH SVHC

- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| | |
|----------------|---|
| Status | Active |
| Category | Quick Disconnects |
| Series | 19276 |
| Description | Quixon Quick Disconnect, InsulKrimp Style, Female, Fully Insulated Blue, 14-16 AWG, Mylar Tap |
| Comments | Low Insertion Force |
| Product Family | Quixon Terminals |
| Product Name | InsulKrimp,Quixon |
| Type | Quick Disconnect |
| UPC | 884982565128 |

Agency

| | |
|-----|---------|
| CSA | LR18689 |
| UL | E79133 |

Electrical

| | |
|-------------------|------|
| Voltage - Maximum | 600V |
|-------------------|------|

Physical

| | |
|---------------|--------|
| Barrel Type | Closed |
| Color - Resin | Blue |
| Flammability | 94V-2 |
| Gender | Female |

| | |
|--------------------------------|-----------------------|
| Glow-Wire Capable | No |
| Insulated | Fully |
| Insulation | Nylon (PA) |
| Lock to Mating Part | None |
| Material - Metal | Brass |
| Material - Plating Mating | Tin |
| Material - Plating Termination | Tin |
| Net Weight | 0.962/g |
| Orientation | Straight |
| Packaging Type | Embossed Tape on Reel |
| Tab Thickness | 0.41mm |
| Tab Width | 7.87mm |
| Temperature Range - Operating | -55° to +105°C |
| Wire Insulation Diameter | 4.06mm |
| Wire Size (AWG) | 14, 16 |

Application Tooling

Global

| Description | Part Number |
|--|-------------------|
| ATP Crimp Dies for the Tape Crimp Module and ATP-101 & 301 Press | <u>0192880105</u> |
| Mini-Mac Applicator | <u>0638854200</u> |