# **Adjustable Tension Levers** 24440.0332



# **Product Description**

#### **Material**

Lever

Steel, blackened

Inner parts Steel, blackened, quality 5.8

Screw

• Steel, blackened, quality 5.8

#### Ball knob

• Thermosetting plastic PF 31, black, DIN 319

# Operation


By lifting the lever the serrations are disengaged. The lever can be positioned by the serrations. On releasing the lever, the serrations are automatically re-engaged.


#### More information

#### **Notes**


The threaded portion can be exchanged.

## Drawing









# **Order information**

d1 d2 I1 d3 d4 d5 h1 h2   [mm]   with screw – picture 2, steel	Dimensions										
· · ·	d2	I <sub>1</sub>	d <sub>3</sub>	d4	d <sub>5</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	I	_	
with screw – picture 2, steel					[mm]				~	[9]	
<b>28 M12 80</b> 19 12 30 48.5 4.5				10	0.0	10.5		4.5	110	320	24440.0332

# Compliance

## **RoHS compliant**

Contains lead - compliant according to exceptions 6a / 6b / 6c

Contains SVHC substances >0,1% w/w Contains lead - SVHC list [REACH] as of 10.06.2022

**Contains Proposition 65 substances** 



Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

# **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.