## **Connection Cable** RJ45 8-pin; Horizontal RJ45 8-pin with Screws



ZAV47V501


Part Number



## **Technical Data**

Mechanical Data			
Connection 1	Plug, straight		
Connection mode 1	RJ45, 8-pin		
Connection 2	Plug, straight		
Connection mode 2	RJ45, 8-pin		
Cable Length	n 5 m		
Cable Diameter	6,2 mm		
Wire cross-section	0,14 mm²		
Temperature Range	070 °C		
Cable Jacket Material	PVC		
Category	CAT 6A		
Packaging unit	1 Piece		
Connection Diagram No.	S81		
Connection Equipment No.	47		

• PVC, straight



Leger	na		PT	Platinum measuring resistor	ENAR5422	Encoder A/Ā (TTL)	
+	Supply Voltage +		пс	not connected	ENBRS422	Encoder B/B (TTL)	
-	Supply Voltage 0 V		U	Test Input	ENA	Encoder A	
~	Supply Voltage (AC Voltage)		Ū	Test Input inverted	ENв	Encoder B	
А	Switching Output	(NO)	W	Trigger Input	Amin	Digital output MIN	
Ā	Switching Output	(NC)	W -	Ground for the Trigger Input	Амах	Digital output MAX	
٧		(NO)	0	Analog Output	Аок	Digital output OK	
V	Contamination/Error Output	(NC)	0-	Ground for the Analog Output	SY In	Synchronization In	
E	Input (analog or digital)		BZ	Block Discharge	SY OUT	Synchronization OUT	
Т	Teach Input		Anv	Valve Output	Out	Brightness output	
Z	Time Delay (activation)		а	Valve Control Output +	м	Maintenance	
S	Shielding		b	Valve Control Output 0 V	rsv	reserved	
RxD	Interface Receive Path		SY	Synchronization	Wire Co	Wire Colors according to DIN IEC 757	
TxD	Interface Send Path		SY-	Ground for the Synchronization	BK	Black	
RDY	Ready		E+	Receiver-Line	BN	Brown	
GND	Ground		S+	Emitter-Line	RD	Red	
CL	Clock		÷	Grounding	OG	Orange	
E/A	Output/Input programmable		SnR	Switching Distance Reduction	YE	Yellow	
0	IO-Link		Rx+/-	Ethernet Receive Path	GN	Green	
PoE	Power over Ethernet		Tx+/-	Ethernet Send Path	BU	Blue	
IN	Safety Input		Bus	Interfaces-Bus A(+)/B(-)	VT	Violet	
OSSD	Safety Output		La	Emitted Light disengageable	GY	Grey	
Signal	Signal Output		Mag	Magnet activation	WH	White	
BI_D+/-	- Ethernet Gigabit bidirect. data	line (A-D)	RES	Input confirmation	PK	Pink	
ENerse	Encoder 0-pulse 0-0 (TTL)		EDM	Contactor Monitoring	GNYE	Green/Yellow	

Specifications are subject to change without notice

## System Components and Software