

DINO-LITE AM7115MZT



The AM7115MZT is part of the universal range and with its standard working distance and wide magnification range from 20 – 220x, it is suitable for a wide range of applications. Because of the built-in polarization filter this model is ideal when working with shiny or reflective objects such as metal, plastic, glass, jewelry, electronics, etc.

The main features of the AM7115MZT are:

- 5 Megapixel Edge sensor
- 20-220x magnification
- integrated polarizer
- Aluminum housing
- Flexible LED Control (FLC)

Model	AM7115MZT
Resolution	5 megapixel (2592x1944)
Magnification	20-220x
Interface	USB 2.0
Nr. of LED's	8
LED on/off switchable	Yes
LED color	White
Housing	Metal housing
Microtouch	Yes
ESD safe	Yes
Output	Picture, video
Video Frame Rate	up to 30 frames-per-second
Measurement	Yes
Calibration	Yes
Diffuser available:	Yes (N3C-D included)
Infrared filter:	IR cut-filter >650 nm
Polarizer:	Yes, linear
Compatibility	Windows XP, Vista, 7, 8 & 10, MacOS 10.9 and up
Software (Included)	DinoCapture 2.0 (Windows), DinoXcope (Mac OS)
Package contents	Microscope, Carry pouch, Software CD, Calibration target, User manual, N3C-O- Open cap, N3C-C- Closed cap, N3C-D- Diffuser cap, N3C-Extension cap, N3C-L- Long cap, N3C-S- Side light cap