

Product type designation

CP 1243-1

Communications processor CP 1243-1 for connection of SIMATIC S7-1200 as additional Ethernet interface and for Connection to control centers via Remote effect protocols (DNP3, IEC 60870, TeleControl Basic), security (Firewall, VPN)



Transmission rate

Transfer rate

- at the 1st interface

10 ... 100 Mbit/s

Interfaces

Number of interfaces / acc. to Industrial Ethernet

1

Number of electrical connections

- at the 1st interface / acc. to Industrial Ethernet
- for power supply

1

0

Type of electrical connection

- at the 1st interface / acc. to Industrial Ethernet

RJ45 port

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage

DC

Supply voltage / 1 / from backplane bus

5 V

Consumed current

- from backplane bus / at DC / at 5 V / typical

0.25 A

Power loss [W]

1.25 W

Permitted ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> • for vertical installation / during operation 	-20 ... +60 °C
<ul style="list-style-type: none"> • for horizontally arranged busbars / during operation 	-20 ... +70 °C
<ul style="list-style-type: none"> • during storage 	-40 ... +70 °C
<ul style="list-style-type: none"> • during transport 	-40 ... +70 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

Module format	Compact module S7-1200 single width
Width	30 mm
Height	110 mm
Depth	75 mm
Net weight	0.122 kg
Mounting type	
<ul style="list-style-type: none"> • 35 mm DIN rail mounting 	Yes
<ul style="list-style-type: none"> • wall mounting 	Yes

Product properties, functions, components / general

Number of units	
<ul style="list-style-type: none"> • per CPU / maximum 	3

Performance data / open communication

Number of possible connections / for open communication	
<ul style="list-style-type: none"> • by means of T blocks / maximum 	like CPU

Performance data / S7 communication

Number of possible connections / for S7 communication	
<ul style="list-style-type: none"> • Note 	like CPU

Performance data / IT functions

Number of possible connections	
<ul style="list-style-type: none"> • as e-mail client / maximum 	1

Performance data / telecontrol

Suitability for use	
<ul style="list-style-type: none"> • Node station 	No
<ul style="list-style-type: none"> • substation 	Yes
<ul style="list-style-type: none"> • TIM control center 	No
Control center connection	For use with TeleControl Server Basic, WinCC and PCS7 supported
<ul style="list-style-type: none"> • by means of a permanent connection 	
<ul style="list-style-type: none"> • Note 	Connection to SCADA system via Telecontrol Server Basic and Standard Telecontrol protocols

Protocol / is supported	
<ul style="list-style-type: none"> • DNP3 • IEC 60870-5 	<p>Yes</p> <p>Yes</p>
Product function / data buffering if connection is aborted	Yes; 64,000 values
Number of data points per station / maximum	200

Performance data / Teleservice

Diagnostics function / online diagnostics with SIMATIC STEP 7	Yes
Product function	
<ul style="list-style-type: none"> • program download with SIMATIC STEP 7 • Remote firmware update 	<p>Yes</p> <p>Yes</p>
Configuration software	
<ul style="list-style-type: none"> • required 	STEP 7 Basic/Professional

Product functions / Diagnosis

Product function / Web-based diagnostics	Yes
--	-----

Product functions / Security

Firewall version	stateful inspection
Product function / with VPN connection	IPSec, SINEMA RC
Type of encryption algorithms / with VPN connection	AES-256, AES-192, AES-128, 3DES-168
Type of authentication procedure / with VPN connection	Preshared key (PSK), X.509v3 certificates
Type of hashing algorithms / with VPN connection	MD5, SHA-1, SHA-2
Number of possible connections / with VPN connection	8
Product function	
<ul style="list-style-type: none"> • password protection for Web applications • password protection for teleservice access • encrypted data transmission • ACL - IP-based • ACL - IP-based for PLC/routing • switch-off of non-required services • Blocking of communication via physical ports • log file for unauthorized access 	<p>No</p> <p>No</p> <p>Yes</p> <p>No</p> <p>No</p> <p>Yes</p> <p>No</p> <p>No</p>

Product functions / Time

Protocol / is supported	
<ul style="list-style-type: none"> • NTP • NTP (secure) 	<p>Yes</p> <p>Yes</p>
time synchronization	
<ul style="list-style-type: none"> • from NTP-server • from control center 	<p>Yes</p> <p>Yes</p>

Further Information / Internet Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL <http://www.siemens.com/snst>
- to website: Industrial communication <http://www.siemens.com/simatic-net>
- to website: Industry Mall <https://mall.industry.siemens.com>
- to website: Information and Download Center <http://www.siemens.com/industry/infocenter>
- to website: Image database <http://automation.siemens.com/bilddb>
- to website: CAx Download Manager <http://www.siemens.com/cax>
- to website: Industry Online Support <https://support.industry.siemens.com>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

12/18/2018