# NC machine reamer HSSE with uniform shank (diameter can be selected)

for universal use up to 1000 N/mm<sup>2</sup>



### Application

for producing fit tolerances in through holes on NC machines or conventional machines up to 1000  $\rm N/mm^2.$ 

#### Version

■ 7-8° left-hand spiral, type B

## Advantage

- Delivered ex stock
- high-quality HSSE cutting material for a very long service life
- good bore hole quality (dimensional tolerance, roundness, surface quality)

[	Application	n Steel (N/mm <sup>2</sup> )			Stainless steel		Alu		Brass		Bronze		Plas-			Titan-			Hard mat.	
		<700	<1000	<1300	marten.	austen.	short	long	short	long	short	long	tics	G(C)FK	GjMW	alloy	alloy	alloy	<55 HRC	<65 HRC
ĺ		12	9	7	8	7	17	17	17	17	13	13			11	5	5			

Art. No.	11625 546					
Cutting material	HSSE					
Tolerance of fit	0 / +0,005 mm					
Groove type	Left-hand twist, 7-8°					
Tool holding device	HA parallel shank					
Min./max. cutting edge diameter	7.06-7.5 mm					
Length	109 mm					
Cutting edge length	31 mm					
Projecting length	72 mm					
Shaft diameter	8 mm					
Number of cutting edges	6 PCS					
f steel 1300	0.12 mm/r					
DIN	Similar to 212					

## EAN-Code

4050293430868

