



Safety Data Sheet

Copyright, 2019, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	11-1458-6	Version number:	14.03
Revision date:	09/09/2019	Supersedes date:	03/05/2019
Transportation version number:	1.00 (12/01/2011)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ SCOTCH-WELD™ Preformed Sealant Black 5313

Product Identification Numbers

FS-5313-0203-2	FS-9000-0277-5	FS-9000-2019-9	FS-9000-2037-1	FS-9000-2079-3
FS-9100-0153-6	FS-9100-0290-6			
7000079781	7000033721	7000033722	7000079797	7000079809
7000079808	7000079786			

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Sealant.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

This material is not classified as hazardous according to Regulation (EC) No. 1272/2008, as amended, on classification, labelling, and packaging of substances and mixtures.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

3M™ SCOTCH-WELD™ Preformed Sealant Black 5313

Not applicable

SUPPLEMENTAL INFORMATION:**Supplemental Hazard Statements:**

EUH210

Safety data sheet available on request.

Notes on labelling

Nota L applied to CASRN 64741-88-4.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification
Butene, polymer with 2-methyl-1-propene	9044-17-1			15 - 40	Substance not classified as hazardous
Carbon black	1333-86-4	215-609-9	01-2119384822-32	10 - 30	Substance with a Community level exposure limit in the workplace
Kaolin	1332-58-7	310-194-1		10 - 30	Substance with a Community level exposure limit in the workplace
Butyl rubber.	9010-85-9			7 - 20	Substance not classified as hazardous
Talc	14807-96-6	238-877-9		3 - 7	Substance with a Community level exposure limit in the workplace
Resin acids and rosin acids, esters with glycerol	8050-31-5	232-482-5	01-2119488167-27	1 - 5	Substance not classified as hazardous
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	265-090-8		1 - 5	Nota L Asp. Tox. 1, H304; EUH066
Quartz	14808-60-7	238-878-4		< 1	STOT RE 1, H372
Titanium dioxide	13463-67-7	236-675-5	01-2119489379-17	0 - 0.5	Substance with a Community level exposure limit in the workplace
Zinc oxide	1314-13-2	215-222-5		0 - 0.1	Aquatic Acute 1, H400,M=1; Aquatic Chronic 1, H410,M=1

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures**4.1. Description of first aid measures**

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Irritant vapours or gases.	During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Observe precautions from other sections.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

For industrial/occupational use only. Not for consumer sale or use. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Kaolin	1332-58-7	UK HSC	TWA (as respirable dust): 2 mg/m ³	
Carbon black	1333-86-4	UK HSC	TWA: 3.5 mg/m ³ ; STEL: 7 mg/m ³	
Titanium dioxide	13463-67-7	UK HSC	TWA(Inhalable):10 mg/m ³ ;TWA(respirable):4 mg/m ³	
Talc	14807-96-6	UK HSC	TWA(as respirable dust):1 mg/m ³	
Quartz	14808-60-7	UK HSC	TWA(respirable):0.1 mg/m ³	

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures:Information on recommended monitoring procedures can be obtained from UK HSC

8.2. Exposure controls**8.2.1. Engineering controls**

Not applicable.

8.2.2. Personal protective equipment (PPE)**Eye/face protection**

None required.

Skin/hand protection

No chemical protective gloves are required.

Respiratory protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance**

Physical state
Colour

Solid.
Black

Specific Physical Form:

Paste

Odor

Odourless

Odour threshold

No data available.

pH

No data available.

Boiling point/boiling range

Not applicable.

Melting point

No data available.

Flammability (solid, gas)

Not classified

Explosive properties

Not classified

Oxidising properties

Not classified

Flash point

≥ 93.3 °C [*Test Method: Closed Cup*]

Autoignition temperature

Not applicable.

Flammable Limits(LEL)

Not applicable.

Flammable Limits(UEL)

Not applicable.

Vapour pressure

Not applicable.

Relative density

1.25 - 1.35 [*Ref Std: WATER=1*]

Water solubility

Nil

Solubility- non-water

No data available.

Partition coefficient: n-octanol/water

No data available.

Evaporation rate

No data available.

Vapour density

Not applicable.

Decomposition temperature

No data available.

Viscosity

No data available.

Density

1.25 - 1.35 g/ml

9.2. Other information

EU Volatile Organic Compounds

No data available.

Percent volatile

0 %

SECTION 10: Stability and reactivity**10.1 Reactivity**

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

3M™ SCOTCH-WELD™ Preformed Sealant Black 5313

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

No known health effects.

Skin contact

Contact with the skin during product use is not expected to result in significant irritation.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Kaolin	Dermal		LD50 estimated to be > 5,000 mg/kg
Kaolin	Ingestion	Human	LD50 > 15,000 mg/kg
Carbon black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon black	Ingestion	Rat	LD50 > 8,000 mg/kg
Butyl rubber.	Dermal		LD50 estimated to be > 5,000 mg/kg
Butyl rubber.	Ingestion		LD50 estimated to be > 5,000 mg/kg
Talc	Dermal		LD50 estimated to be > 5,000 mg/kg
Talc	Ingestion		LD50 estimated to be > 5,000 mg/kg
Distillates (petroleum), solvent-refined heavy paraffinic	Dermal	Rabbit	LD50 > 2,000 mg/kg
Distillates (petroleum), solvent-refined heavy paraffinic	Ingestion	Rat	LD50 > 5,000
Resin acids and rosin acids, esters with glycerol	Dermal	Rabbit	LD50 > 5,000 mg/kg
Resin acids and rosin acids, esters with glycerol	Ingestion	Rat	LD50 > 2,000 mg/kg
Quartz	Dermal		LD50 estimated to be > 5,000 mg/kg
Quartz	Ingestion		LD50 estimated to be > 5,000 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg

3M™ SCOTCH-WELD™ Preformed Sealant Black 5313

Titanium dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Zinc oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Zinc oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.7 mg/l
Zinc oxide	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Kaolin	Professional judgement	No significant irritation
Carbon black	Rabbit	No significant irritation
Butyl rubber.	Rabbit	No significant irritation
Distillates (petroleum), solvent-refined heavy paraffinic	Rabbit	Minimal irritation
Talc	Rabbit	No significant irritation
Resin acids and rosin acids, esters with glycerol	Rabbit	Minimal irritation
Quartz	Professional judgement	No significant irritation
Titanium dioxide	Rabbit	No significant irritation
Zinc oxide	Human and animal	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Kaolin	Professional judgement	No significant irritation
Carbon black	Rabbit	No significant irritation
Butyl rubber.	Professional judgement	No significant irritation
Distillates (petroleum), solvent-refined heavy paraffinic	Rabbit	Mild irritant
Talc	Rabbit	No significant irritation
Resin acids and rosin acids, esters with glycerol	Rabbit	Mild irritant
Titanium dioxide	Rabbit	No significant irritation
Zinc oxide	Rabbit	Mild irritant

Skin Sensitisation

Name	Species	Value
Distillates (petroleum), solvent-refined heavy paraffinic	Guinea pig	Not classified
Resin acids and rosin acids, esters with glycerol	Guinea pig	Not classified
Titanium dioxide	Human and animal	Not classified
Zinc oxide	Guinea pig	Not classified

Respiratory Sensitisation

3M™ SCOTCH-WELD™ Preformed Sealant Black 5313

Name	Species	Value
Talc	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
Carbon black	In Vitro	Not mutagenic
Carbon black	In vivo	Some positive data exist, but the data are not sufficient for classification
Distillates (petroleum), solvent-refined heavy paraffinic	In Vitro	Some positive data exist, but the data are not sufficient for classification
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic
Resin acids and rosin acids, esters with glycerol	In Vitro	Not mutagenic
Quartz	In Vitro	Some positive data exist, but the data are not sufficient for classification
Quartz	In vivo	Some positive data exist, but the data are not sufficient for classification
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic
Zinc oxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
Zinc oxide	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Kaolin	Inhalation	Multiple animal species	Not carcinogenic
Carbon black	Dermal	Mouse	Not carcinogenic
Carbon black	Ingestion	Mouse	Not carcinogenic
Carbon black	Inhalation	Rat	Carcinogenic.
Distillates (petroleum), solvent-refined heavy paraffinic	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Talc	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Quartz	Inhalation	Human and animal	Carcinogenic.
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.

Reproductive Toxicity
Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Talc	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesis
Zinc oxide	Ingestion	Not classified for reproduction and/or development	Multiple animal species	NOAEL 125 mg/kg/day	premating & during gestation

Target Organ(s)
Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Distillates (petroleum), solvent-refined heavy	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and	NOAEL Not available	

3M™ SCOTCH-WELD™ Preformed Sealant Black 5313

paraffinic				animal		
Distillates (petroleum), solvent-refined heavy paraffinic	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Kaolin	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL NA	occupational exposure
Kaolin	Inhalation	pulmonary fibrosis	Not classified	Rat	NOAEL Not available	
Carbon black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Distillates (petroleum), solvent-refined heavy paraffinic	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.21 mg/l	28 days
Talc	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pulmonary fibrosis respiratory system	Not classified	Rat	NOAEL 18 mg/m3	113 weeks
Resin acids and rosin acids, esters with glycerol	Ingestion	liver heart skin endocrine system bone, teeth, nails, and/or hair blood bone marrow hematopoietic system immune system muscles nervous system eyes kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 5,000 mg/kg/day	90 days
Quartz	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Zinc oxide	Ingestion	nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	10 days
Zinc oxide	Ingestion	endocrine system hematopoietic system kidney and/or bladder	Not classified	Other	NOAEL 500 mg/kg/day	6 months

Aspiration Hazard

Name	Value
Distillates (petroleum), solvent-refined heavy paraffinic	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

3M™ SCOTCH-WELD™ Preformed Sealant Black 5313

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Butene, polymer with 2-methyl-1-propene	9044-17-1		Data not available or insufficient for classification			
Carbon black	1333-86-4		Data not available or insufficient for classification			
Kaolin	1332-58-7	Water flea	Experimental	48 hours	LC50	>1,100 mg/l
Butyl rubber.	9010-85-9		Data not available or insufficient for classification			
Talc	14807-96-6		Data not available or insufficient for classification			
Resin acids and rosin acids, esters with glycerol	8050-31-5	Fathead minnow	Estimated	96 hours	Lethal Level 50%	>100 mg/l
Resin acids and rosin acids, esters with glycerol	8050-31-5	Green Algae	Estimated	72 hours	Effect Level 50%	>100 mg/l
Resin acids and rosin acids, esters with glycerol	8050-31-5	Water flea	Estimated	48 hours	Effect Level 50%	>100 mg/l
Resin acids and rosin acids, esters with glycerol	8050-31-5	Green Algae	Estimated	72 hours	No obs Effect Level	>100 mg/l
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	Fathead minnow	Estimated	96 hours	Lethal Level 50%	>100 mg/l
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	Water flea	Estimated	48 hours	EC50	>100 mg/l
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	Green algae	Experimental	96 hours	Effect Level 50%	>100 mg/l
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	Green algae	Experimental	96 hours	No obs Effect Level	100 mg/l
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	Water flea	Experimental	21 days	No obs Effect Level	100 mg/l
Quartz	14808-60-7	Green Algae	Estimated	72 hours	EC50	440 mg/l
Quartz	14808-60-7	Water flea	Estimated	48 hours	EC50	7,600 mg/l
Quartz	14808-60-7	Zebra Fish	Estimated	96 hours	LC50	5,000 mg/l
Quartz	14808-60-7	Green Algae	Estimated	72 hours	NOEC	60 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
Zinc oxide	1314-13-2	Rainbow trout	Estimated	96 hours	LC50	0.21 mg/l
Zinc oxide	1314-13-2	Crustacea other	Experimental	24 hours	LC50	0.24 mg/l
Zinc oxide	1314-13-2	Green Algae	Experimental	72 hours	EC50	0.057 mg/l

3M™ SCOTCH-WELD™ Preformed Sealant Black 5313

Zinc oxide	1314-13-2	Algae or other aquatic plants	Estimated	96 hours	Effect Concentration 10%	0.026 mg/l
Zinc oxide	1314-13-2	Crustacea other	Estimated	24 days	NOEC	0.007 mg/l
Zinc oxide	1314-13-2	Rainbow trout	Estimated	30 days	NOEC	0.049 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Butene, polymer with 2-methyl-1-propene	9044-17-1	Data not available or insufficient			N/A	
Carbon black	1333-86-4	Data not available or insufficient			N/A	
Kaolin	1332-58-7	Data not available or insufficient			N/A	
Butyl rubber.	9010-85-9	Data not available or insufficient			N/A	
Talc	14807-96-6	Data not available or insufficient			N/A	
Resin acids and rosin acids, esters with glycerol	8050-31-5	Experimental Biodegradation	28 days	CO2 evolution	0 % weight	OECD 301B - Modified sturm or CO2
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	Experimental Biodegradation	28 days	CO2 evolution	22 % weight	OECD 301B - Modified sturm or CO2
Quartz	14808-60-7	Data not available or insufficient			N/A	
Titanium dioxide	13463-67-7	Data not available or insufficient			N/A	
Zinc oxide	1314-13-2	Data not available or insufficient			N/A	

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Butene, polymer with 2-methyl-1-propene	9044-17-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Carbon black	1333-86-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Kaolin	1332-58-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Butyl rubber.	9010-85-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Talc	14807-96-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Resin acids and rosin acids, esters with glycerol	8050-31-5	Experimental Bioconcentration		Log Kow	<1.5	Other methods
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	Estimated Bioconcentration		Bioaccumulation factor	7.5	Estimated: Bioconcentration factor
Quartz	14808-60-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Experimental BCF-Carp	42 days	Bioaccumulation factor	9.6	Other methods
Zinc oxide	1314-13-2	Experimental BCF-Carp	56 days	Bioaccumulation factor	≤217	OECD 305E - Bioaccumulation flow-through fish test

12.4. Mobility in soil

3M™ SCOTCH-WELD™ Preformed Sealant Black 5313

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

This product has been classified as a non-hazardous waste. Prior to disposal, consult all applicable authorities and regulations to insure proper classification. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product may be placed in a landfill properly designed for industrial waste.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 10	Waste adhesives and sealants other than those mentioned in 08 04 09
20 01 28	Paint, inks, adhesives and resins other than those mentioned in 20 01 27

SECTION 14: Transportation information

FS-5313-0203-2, FS-9000-0277-5, FS-9000-2019-9, FS-9000-2037-1,
FS-9000-2079-3, FS-9100-0153-6, FS-9100-0290-6

Not hazardous for transportation

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
Carbon black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Quartz	14808-60-7	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained

substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H304	May be fatal if swallowed and enters airways.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Revision information:

Section 3: Composition/ Information of ingredients table information was modified.

Section 09: Color information was added.

Section 09: Odor information was added.

Sections 3 and 9: Odour, colour, grade information information was deleted.

Section 12: Component ecotoxicity information information was modified.

Section 15: Regulations - Inventories information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M United Kingdom MSDSs are available at www.3M.com/uk