Multi-range thread milling cutter solid carbide TIAIN (M/MF) with radial internal cooling straight shank HA for universal use up to 1500 N/mm2 in female threads



Application

For producing **metric** right-hand and left-hand threads on CNC machines in through holes and blind holes in the steel, stainless steel, non-ferrous metals, cast iron and special alloy material groups up to a certain strength.

Version

■ Precision-ground thread milling cutter

Advantage

Innovative cutting geometry for very high dimensional accuracy, process reliability and chip removal.

A	Application	Steel (N/mm²)			Stainless steel		Alu		Brass					Graphite					Hard mat.	
		<700	<1000	<1300	marten.	austen.	short	long	short	long	short	long	tics	G(C)FK	GjMW	alloy	alloy	alloy	<55 HRC	<65 HRC
		120	110	90		80	220	240			180	180	220	150	90	50	40	40		

Art. no.	13496 224					
Cutting material	VHM					
Surface	TiAIN					
Coolant supply	Internal radial					
Tool holding device	HA parallel shank					
Cutting edge diameter	10 mm					
Pitch	1.5 mm					
Suitable for metric fine threads from	MF14					
Length	73 mm					
Cutting edge length	21.8 mm					
Shaft diameter	10 mm					
Number of cutting edges	4 PCS					
f steel 1000	0.08 mm/r					

EAN-Code

4050293263909

