

Part Number: 2162701052

Product Description: SL Female-to-SL Female Off-the-Shelf (OTS) Cable Assembly, Positive Lock, Single Row, 150.00mm Length, Tin (Sn) Plating, 5 Circuits, Black

Series Number: 216270

Status: Active

Product Category: Power and Signal Cable

Assemblies



Documents & Resources

Drawings

2162701052_sd.pdf

3D Models and Design Files

2162701052_stp.zip

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|---------------------------------------------------|
| China RoHS | © |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2- 21 |
| REACH SVHC | Not Contained per D(2024)6225-DC (07 Nov 2024) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

Part Details

General

| Status | Active |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| Category | Power and Signal Cable Assemblies |
| Series | 216270 |
| Description | SL Female-to-SL Female Off-the- Shelf (OTS) Cable Assembly, Positive Lock, Single Row, 150.00mm Length, Tin (Sn) Plating, 5 Circuits, Black |
| Application | Signal, Wire-to-Board, Wire-to-Wire |
| Assembly Configuration | Dual Ended Connectors |
| Connector to Connector | SL-to-SL |
| Product Name | SL |
| Туре | Discrete Wire Assembly |
| UPC | 193264730711 |

Electrical

| Current - Maximum per Contact | 3.0A |
|-------------------------------|------------|
| Voltage - Maximum | 600V AC/DC |

Physical

| Cable Length | 150.00mm |
|--------------------------------|-----------------|
| Circuits (Loaded) | 5 |
| Circuits (maximum) | 5 |
| Color - Resin | Black |
| Gender | Female-Female |
| Lock to Mating Part | Yes |
| Material - Metal | Phosphor Bronze |
| Material - Plating Mating | Tin |
| Material - Plating Termination | Tin |
| Material - Resin | Polyester Alloy |
| Net Weight | 5.596/g |

| Number of Rows | 1 |
|-----------------------------|----------------------|
| Overmolded | No |
| Packaging Type | Bag |
| Pitch - Mating Interface | 2.54mm |
| Single Ended | No |
| Termination Interface Style | Crimp or Compression |
| Wire/Cable Type | UL 11028 |
| Wire Insulation Diameter | 1.63mm max. |
| Wire Size (AWG) | 22 |

Mates With / Use With

Mates with Part(s)

| Description | Part Number |
|-------------------------------------------------------------------|--------------|
| SL Single Row Housing Panel Mounts | 70018 |
| SL Single Row Crimp Housings | <u>70107</u> |
| SL Vertical Single Row Headers | <u>70541</u> |
| SL Vertical Single Row Headers | 70543 |
| SL Vertical Single Row Headers | 70545 |
| SL Vertical, Single Row, Surface Mount Headers | 74099 |
| SL Right-Angle Single Row Headers | <u>70551</u> |
| SL Right-Angle, Single Row, Low Profile Headers | 70553 |
| SL Right-Angle Single Row Headers | <u>70555</u> |
| SL Right-Angle, Single Row, Low Profile, Surface Mount Headers | 70634 |