

Kvalitet / Quality / Qualität:
442

Vægt / Weight / Gewicht	g/m ²	270	EN 12127
Komposition / Composition / Gewebemischung	%	65/35 pes/co	
Konstruktion / Construction / Webkonstruktion	3/1 Twill		

STYRKE / PHYSICAL PROPERTIES / FESTIGKEIT

Slidstyrke / Abrasion resistance / Strapazierfähigkeit	t	60.000	EN ISO 12947-2
Brudstyrke, kæde / Tensile, warp/ Bruchfestigkeit, Kette	N.	1.600	EN ISO 13394-1
Brudstyrke skud / Tensile, weft/ Bruchfestigkeit, Schuss	N.	1.100	EN ISO 13394-1
Rivstyrke, kæde / Tearing strength, warp/ Reissfestigkeit, Kette	N.	40	EN ISO 13937-2
Rivstyrke, skud / Tearing strength, weft/ Reissfestigkeit, Schuss	N.	38	EN ISO 13937-2

FARVEÆGTHEDER / COLOUR FASTNESS / FARBECHTHEIT

Vaskeægted afsmitning / Fastness to washing staining / Waschechtheit Anbluten	Note	4-5	ISO 105-C06
Svedægted afsmitning/ Fastness to perspiration staining/ Schweissechtheit Anbluten	Note	4-5	ISO 105-E04
Gnidægted, våd / Fastness to rubbing, wet / Reibecktheit, nass	Note	3-4	ISO 105-X12
Gnidægted, tør / Fastness to rubbing, dry / Reibecktheit, trocken	Note	4-5	ISO 105-X12

GENERELLE EGENSKABER / CHARACTERISTICS IN GENERAL / ALLGEMEINE EIGENSCHAFTEN

Dimensionsstabilitet / Dimensional stability / Dimensionsstabilität	%	+/- 1	ISO 6330
Dimensionsstabilitet / Dimensional stability / Dimensionsstabilität	%	+/- 2	ISO 15797 (8B)

Certifikater / Certificates / Zertifikate			
---	--	--	--

Vaskesymboler/ Carelabel/ Pflegesymbole			
---	--	--	--

Vandsøjle / Water resistance / Wassersäule	mm H ₂ O	-	ISO 20811
Åndbarhed / Water vapour permeability / Atmungsaktivität	g/m ² /24 hrs	-	CUP METHOD

Finish / Finish / Ausführung	-		
------------------------------	---	--	--

Bemærkninger / Remarks / Bemerkungen:

based on: 35442 / 37442 / 38442 / 60442
 date period: 1/1-14 => 05/7-16