

RFID Keyfob DROP

iDTRONIC keyfobs combine the RFID technology with good looking and practical keyfob housings. They can easily be fitted to a normal key ring. They are available with the most common ICs in 125 kHz as well as in 13.56 MHz.



Applications:

- Access Control
- Identification
- Time Attendance

Product specification:

Dimensions:	53 x 33 x 4 mm
Weight:	7 g
Material:	Polycarbonate
Colours:	black, blue, red, green, yellow
Surface:	white
Application temp. :	-25 °C to +65 °C

Available 125 kHz systems:

IC Type	Memory	Mode
EM 4100/4200	8 byte	Read Only
EM 4450/4550	125 byte	R/W
Atmel Temic 5567	28 byte	R/W
NXP Hitag1	256 byte	R/W
NXP Hitag2	32 byte	R/W
NXP HitagS	64 / 256 byte	R/W

Available 13.56 MHz systems:

IC Type	ISO	Memory
NXP MIFARE Ultralight®	14443A	64 Bytes
NXP MIFARE® Classic 1K EV1	14443A	1024 Bytes
NXP MIFARE® Classic 4K	14443A	4096 Bytes
NXP MIFARE® DESFire® EV1	14443A	-
NXP I-Code SLI	15693	64 Bytes
NXP I-Code SLI-S	15693	256 Bytes
LEGIC MIM256	-	256 Bytes
LEGIC MIM1024	-	1024 Bytes