Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

WD-40®BIKE® Degreaser

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Universal cleaner

Uses advised against: No information available at present.

1.3 Details of the supplier of the safety data sheet

WD-40 Company Limited, PO Box 440, Kiln Farm, Milton Keynes, MK11 3LF, United Kingdom Phone:+44 (0) 1908 555400, Fax:+44 (0) 1908 266900 www.wd40.co.uk

P.R. Rielly Limited KarKraft House, Kilbarrack Industrial Estate, Kilbarrack, Dublin 5, Ireland Phone:01-832 0006, Fax:01-832 0016 web@team.ie

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.: +353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week) +353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (WDC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
STOT SE	3	H336-May cause drowsiness or dizziness.
Aerosol	1	H222-Extremely flammable aerosol.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Aerosol	1	H229-Pressurised container: May burst if heated.

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H336-May cause drowsiness or dizziness. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area.

P312-Call a POISON CENTRE / doctor if you feel unwell.

P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501-Dispose of contents / container safely.

EUH066-Repeated exposure may cause skin dryness or cracking.

Without adequate ventilation, formation of explosive mixtures may be possible. Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics Propan-2-ol

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %). The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

Danger of bursting (explosion) when heated

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substance

n.a. 3.2 Mixture

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2%	
aromatics	
Registration number (REACH)	01-2119463258-33-XXXX
Index	
EINECS, ELINCS, NLP	919-857-5 (REACH-IT List-No.)
CAS	
content %	70-80
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226
	Asp. Tox. 1, H304
	STOT SE 3, H336

XX

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16. The substances named in this section are given with their actual, appropriate classification! GB (RL) -

Page 3 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 07.03.2017 / 0003 Replacing version dated / version: 10.07.2015 / 0002 Valid from: 07.03.2017 PDF print date: 09.03.2017 WD-40®BIKE® Degreaser

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Typically no exposure pathway.

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Danger of aspiration

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur: Irritation of the respiratory tract Coughing Headaches Dizziness Effects/damages the central nervous system Coordination disorders with long-term contact: Product removes fat. Drying of the skin. Dermatitis (skin inflammation) Ingestion: Nausea Vomiting Danger of aspiration Oedema of the lungs Other dangerous properties cannot be ruled out. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. 4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media CO2 Extinction powder Water jet spray Alcohol resistant foam Unsuitable extinguishing media High volume water jet 5.2 Special hazards arising from the substance or mixture In case of fire the following can develop:

Oxides of carbon

GB (RL)

Toxic pyrolysis products. Danger of explosion by prolonged heating. Explosive vapour/air mixture Dangerous vapours heavier than air. In case of spreading near the ground, flashback to distance sources of ignition is possible. **5.3 Advice for firefighters** In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke. Ensure sufficient supply of air. Avoid inhalation, and contact with eyes or skin. If applicable, caution - risk of slipping.

6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available. Without adequate ventilation, formation of explosive mixtures may be possible. Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling 7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Avoid contact with eyes or skin.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Do not store with flammable or self-igniting materials.

Observe special regulations for aerosols!

Store cool.

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place.

Observe special storage conditions.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

Chemical Name	Hydrocarbons,	C9-C11, n-alkanes, isoalkanes, cy	clics, < 2% aromatics	5	Content %:70- 80
WEL-TWA: 800 mg/m3		WEL-STEL:			
Monitoring procedures:	- - -	Draeger - Hydrocarbons 2/a (81 Draeger - Hydrocarbons 0,1%/c Compur - KITA-187 S (551 174)	(81 03 571)		
BMGV:			Other information: method, EH40)	(WEL acc	c. to RCP-
Chemical Name	· ·	C9-C11, n-alkanes, isoalkanes, cy	•	6	Content %:70- 80
OELV-8h: 100 ppm (573 mg/m3	3) (White Spirit)	OELV-15min: 125 ppm (720 Spirit)	• / (
Monitoring procedures:	-	Draeger - Hydrocarbons 2/a (81 Draeger - Hydrocarbons 0,1%/c Compur - KITA-187 S (551 174)	(81 03 571)		
BLV:			Other information:		
Chemical Name	Petroleum gase	· · ·			Content %:0,1- <29
WEL-TWA: 1000 ppm (1750 mg petroleum gas (LPG))	g/m3) (Liquefied	WEL-STEL: 1250 ppm (218 petroleum gas (LPG))	0 mg/m3) (Liquefied		
Monitoring procedures:			<u> </u>		
BMGV:			Other information:		
Chemical Name	Petroleum gase	es, liquified			Content %:0,1- <29
OELV-8h: 1000 ppm (1800 mg/	m3)	OELV-15min: 1250 ppm (22	50 mg/m3)		
Monitoring procedures:			<u></u>		
BLV:			Other information:		
Chemical Name	Propan-2-ol				Content %:1-5
WEL-TWA: 400 ppm (999 mg/m	n3)	WEL-STEL: 500 ppm (1250			
Monitoring procedures:	-	Compur - KITA-122 SA(C) (549 2	277)		
	-	Compur - KITA-150 U (550 382) Draeger - Alcohol 25/a i-Propano			
	-	DFG (D) (Loesungsmittelgemisch		mixtures	6) - 1008 2002 -
	-	EU project BC/CEN/ENTR/000/2			0) 1000, 2002
	-	Draeger - Alcohol 100/a (CH 29 7		• .,	
BMGV:		v	Other information:		
Chemical Name	Propan-2-ol				Content %:1-5
OELV-8h: 200 ppm		OELV-15min: 400 ppm			
Monitoring procedures:	-	Compur - KITA-122 SA(C) (549 2	277)		
	-	Compur - KITA-150 U (550 382)			
	-	Draeger - Alcohol 25/a i-Propand			A000 0000
		DFG (D) (Loesungsmittelgemisch EU project BC/CEN/ENTR/000/2			6) - 1998, 2002 -
	-	Draeger - Alcohol 100/a (CH 29 7		04)	
BLV: 40 mg/l (acetone, U, d) (A	CGIH-BEI)		Other information:	Sk	
	/				

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

OELV-8h = Occupational Exposure Limit Value (8-hour reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction. | OELV-15min = Occupational Exposure Limit Value (15-minute reference period). (IFV) =

Page 6 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 07.03.2017 / 0003 Replacing version dated / version: 10.07.2015 / 0002 Valid from: 07.03.2017 PDF print date: 09.03.2017 WD-40®BIKE® Degreaser

GBRL

Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction. | BLV = Biological limit value | Other information: Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.

Propan-2-ol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note
	Environment - freshwater		PNEC	140,9	mg/l	
	Environment - marine		PNEC	140,9	mg/l	
	Environment - sediment, freshwater		PNEC	552	mg/kg	
	Environment - sediment, marine		PNEC	552	mg/kg	
	Environment - soil		PNEC	28	mg/kg	
	Environment - sewage treatment plant		PNEC	2251	mg/l	
Consumer	Human - dermal	Long term	DNEL	319	mg/kg	(1 d)
Consumer	Human - inhalation	Long term	DNEL	89	mg/m3	
Consumer	Human - oral	Long term	DNEL	26	mg/kg	(1 d)
Workers / employees	Human - dermal	Long term	DNEL	888	mg/kg	(1 d)
Workers / employees	Human - inhalation	Long term	DNEL	500	mg/m3	

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics								
Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note		
Consumer	Human - oral	Long term, systemic effects	DNEL	300	mg/kg bw/day			
Consumer	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg bw/day			
Consumer	Human - inhalation	Long term, systemic effects	DNEL	900	mg/m3			
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg bw/day			
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	1500	mg/m3			

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and nonmetrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Solvent resistant protective gloves (EN 374). If applicable Protective Neoprene® / polychloroprene gloves (EN 374). (B) (R) Page 7 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 07.03.2017 / 0003 Replacing version dated / version: 10.07.2015 / 0002 Valid from: 07.03.2017 PDF print date: 09.03.2017 WD-40(BIKE) Degreaser

Protective nitrile gloves (EN 374) Minimum layer thickness in mm: 0,4 Permeation time (penetration time) in minutes:

> 480 The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary. If OES or MEL is exceeded. Filter A2 P2 (EN 14387), code colour brown, white At high concentrations: Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138) Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

err mernanen en baele prijelear and enen	
Physical state:	Aerosol. Active substance: liquid.
Colour:	Colourless
Odour:	Solvent
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	n.a.
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Vapours heavier than air.
Density:	Not determined
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Not miscible
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Possible build up of explosive/highly flammable vapour/air
	mixture. Product is not explosive.
Oxidising properties:	No
9.2 Other information	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined

Conductivity: Surface tension: Solvents content: Not determined Not determined Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. **10.3 Possibility of hazardous reactions** No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources Pressure increase will result in danger of bursting.

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

WD-40®BIKE® Degreaser						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal						n.d.a.
route:						
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-						
RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification
						according to
						calculation
						procedure.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute			
					Oral Toxicity)			
Acute toxicity, by dermal	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute			
route:					Dermal Toxicity)			
Acute toxicity, by inhalation:	LC50	>5000	mg/m3/8	Rat	OECD 403 (Acute			
			h		Inhalation Toxicity)			

Skin corrosion/irritation:	Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Repeated exposure may cause skin
Serious eye	Rabbit	OECD 405 (Acute	dryness or cracking. Not irritant
damage/irritation:		Eye Irritation/Corrosion)	
Respiratory or skin sensitisation:	Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:		OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:		OECD 453 (Combined Chronic Toxicity/Carcinogenicit y Studies)	Negative, Analogous conclusion
Reproductive toxicity:		OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Specific target organ toxicity - single exposure (STOT-SE):			May cause drowsiness or dizziness.
Aspiration hazard:			Yes
Symptoms:			unconsciousnes s, headaches, dizziness, reddening of the skin
Symptoms:			unconsciousnes s, headaches, dizziness, discoloration of the skin, vomiting, diarrhoea
Specific target organ toxicity - repeated exposure (STOT- RE), oral:		OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Not to be expected

Petroleum gases, liquified						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	>5	mg/l			
Skin corrosion/irritation:						Not irritant
Serious eye						Not irritant
damage/irritation:						

Propan-2-ol Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4570-5840	mg/kg	Rat	OECD 401 (Acute	
					Oral Toxicity)	
Acute toxicity, by dermal	LD50	13900	mg/kg	Rabbit	OECD 402 (Acute	
route:					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	30	mg/l/4h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye				Rabbit	OECD 405 (Acute	Eye Irrit. 2
damage/irritation:					Eye	
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	
Germ cell mutagenicity:				Salmonella	(Ames-Test)	Negative
				typhimurium		
Carcinogenicity:						Negative

.GB (RL)				
Page 10 of 16 Safety data sheet according to Revision date / version: 07.03.2 Replacing version dated / versi Valid from: 07.03.2017 PDF print date: 09.03.2017 WD-40®BIKE® Degreaser	2017 / 0003	16, Annex II		
Reproductive toxicity:				
Specific target organ toxicity - repeated exposure (STOT- RE):				
Symptoms:				

R⊑).						
Symptoms:						breathing difficulties, unconsciousnes s, vomiting, headaches, fatigue, dizziness, nausea
Specific target organ toxicity - repeated exposure (STOT- RE), oral:	NOAEL	900	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	

Negative Target organ(s): liver

SECTION 12: Ecological information

ND-40®BIKE® Degrea Foxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to							n.d.a.
daphnia:							
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							The
degradability:							surfactant(s) contained in this mixture complies(comp y) with the biodegradabilit criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to suppor this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer. Isolate as much as possible with
							an oil separato
2.3. Bioaccumulative							n.d.a.
otential:							
2.4. Mobility in soil:							n.d.a.
2.5. Results of PBT and vPvB assessment							n.d.a.
2.6. Other adverse							n.d.a.

Other information:							According to the recipe, contains no
							AOX.
				00/	(!		
Hydrocarbons, C9-C11 Toxicity / effect			Value			Test wetherd	Nataa
	Endpoint	Time 96h		Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus	OECD 203	
					mykiss	(Fish, Acute	
12.1. Toxicity to fish:	NOELR	28d	0,13	mg/l	Oncorhynchus	Toxicity Test) QSAR	
12.1. Toxicity to fish:	NUELK	280	0,13	mg/i		QSAR	
10.1 Taviaitu ta	EC50	48h	>1000		mykiss Danknie megne	OECD 202	
12.1. Toxicity to	ECSU	48N	>1000	mg/l	Daphnia magna		
daphnia:						(Daphnia sp. Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to	NOELR	21d	0,23	mg/l	Daphnia magna	QSAR	
daphnia:	NOLLI	210	0,23	ing/i	Daprina magna	QUAN	
12.1. Toxicity to algae:	NOELR	72h	100	mg/l	Pseudokirchnerie	OECD 201	
12.1. Toxicity to digue.	NOLEN	7211	100	iiig/i	lla subcapitata	(Alga, Growth	
					na ouooaphala	Inhibition Test)	
12.1. Toxicity to algae:	ErC50	72h	>1000	mg/l	Pseudokirchnerie	OECD 201	
12.11 Toxicity to algue.	2.000		1000	g/i	lla subcapitata	(Alga, Growth	
						Inhibition Test)	
12.1. Toxicity to algae:	EbC50	72h	>1000	mg/l	Pseudokirchnerie	OECD 201	
					lla subcapitata	(Alga, Growth	
						Inhibition Test)	
12.1. Toxicity to algae:	ErC50	72h	>1000	mg/l	Pseudokirchnerie	OECD 201	
, ,				U	lla subcapitata	(Alga, Growth	
						Inhibition Test)	
12.1. Toxicity to algae:	EbC50	72h	>1000	mg/l	Pseudokirchnerie	OECD 201	
					lla subcapitata	(Alga, Growth	
						Inhibition Test)	
12.1. Toxicity to algae:	NOELR	72h	100	mg/l	Raphidocelis	OECD 201	
					subcapitata	(Alga, Growth	
						Inhibition Test)	
12.2. Persistence and		28d	80	%		OECD 301 F	Readily
degradability:						(Ready	biodegradabl
						Biodegradability -	
						Manometric	
						Respirometry	
						Test)	
12.5. Results of PBT							No PBT
and vPvB assessment							substance, N
							vPvB substar

Petroleum gases, liquified							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative							No
potential:							

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	1400	mg/l	Lepomis macrochirus		
12.1. Toxicity to daphnia:	EC50	48h	2285	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Desmodesmus subspicatus		
12.2. Persistence and degradability:		21d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	

12.2. Persistence and degradability:		99,9	%		OECD 303 A (Simulation Test - Aerobic Sewage Treatment - Activated Sludge Units)	
12.3. Bioaccumulative potential:	Log Pow	0,05			OECD 107 (Partition Coefficient (n- octanol/water) - Shake Flask Method)	
12.4. Mobility in soil:	Koc	1,1				expert judgement
12.5. Results of PBT and vPvB assessment						No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	>1000	mg/l	activated sludge		
Other information:	ThOD	2,4	g/g			
Other information:	BOD5	53	%			
Other information:	COD	96	%			References
Other information:	COD	2,4	g/g			
Other information:	BOD5	53	%			
Other information:	BOD	1171	mg/g			

SECTION 13: Disposal considerations

13.1 Waste treatment methods For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances 20 01 29 detergents containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

Recycling

15 01 04 metallic packaging

SECTION 14: Transport information

General statements 14.1. UN number: Transport by road/by rail (ADR/RID) 14.2. UN proper shipping name: UN 1950 AEROSOLS 14.3. Transport hazard class(es): 14.4. Packing group: Classification code:	1950 2.1 - 5F	۲
LQ: 14.5. Environmental hazards: Tunnel restriction code: Transport by sea (IMDG-code) 14.2. UN proper shipping name: AEROSOLS 14.3. Transport hazard class(es): 14.4. Packing group:	1 L Not applicable D	٠

WD-40®BIKE® Degreaser					
EmS: Marine Pollutant: 14.5. Environmental hazards: Transport by air (IATA) 14.2. UN proper shipping name: Aerosols, flammable	F-D, S-U n.a Not applicable				
14.3. Transport hazard class(es): 14.4. Packing group:	2.1 -	(
14.5. Environmental hazards: Not applicable 14.6. Special precautions for user Not applicable					
Persons employed in transporting dangerous goods must be trained. All persons involved in transporting must observe safety regulations. Precautions must be taken to prevent damage.					
14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code Freighted as packaged goods rather than in bulk, therefore not applicable. Minimum amount regulations have not been taken into account. Danger code and packing code on request. Comply with special provisions.					
SECTION 15: Re	gulatory information				

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Observe restrictions:

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC):

REGULATION (EC) No 648/2004

30 % and more aliphatic hydrocarbons less than 5 % non-ionic surfactants

Observe youth employment law (German regulation).

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

EUF0025 **Revised sections:** 2,16 These details refer to the product as it is delivered. Employee instruction/training in handling hazardous materials is required. Employee training in handling dangerous goods is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
STOT SE 3, H336	Classification according to calculation procedure.
Aerosol 1, H222	Classification based on test data.
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on test data.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3). H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

99.25 %

Page 14 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 07.03.2017 / 0003 Replacing version dated / version: 10.07.2015 / 0002 Valid from: 07.03.2017 PDF print date: 09.03.2017 WD-40®BIKE® Degreaser H220 Extremely flammable gas. STOT SE — Specific target organ toxicity - single exposure - narcotic effects Aerosol — Aerosols Asp. Tox. — Aspiration hazard Flam. Liq. — Flammable liquid Flam. Gas — Flammable gases (including chemically unstable gases) Eye Irrit. — Eye irritation Any abbreviations and acronyms used in this document: AC **Article Categories** acc., acc. to according, according to ACGIHAmerican Conference of Governmental Industrial Hygienists ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOEL Acceptable Operator Exposure Level AOX Adsorbable organic halogen compounds approximately approx. Art., Art. no. Article number ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP) BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF Bioconcentration factor BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation) BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BMGV Biological monitoring guidance value (EH40, UK) BOD Biochemical oxygen demand BSEF Bromine Science and Environmental Forum bw body weight Chemical Abstracts Service CAS CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques CIPAC Collaborative International Pesticides Analytical Council CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic COD Chemical oxygen demand CTFA Cosmetic, Toiletry, and Fragrance Association DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon DT50 Dwell Time - 50% reduction of start concentration DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes) dry weight dw for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EĊ European Community ECHA European Chemicals Agency EEA European Economic Area European Economic Community EEC European Inventory of Existing Commercial Chemical Substances EINECS ELINCS European List of Notified Chemical Substances ΕN European Norms EPA United States Environmental Protection Agency (United States of America) ERC Environmental Release Categories ES Exposure scenario et cetera etc. EU **European Union** EWC European Waste Catalogue Fax number Fax. gen. general Globally Harmonized System of Classification and Labelling of Chemicals GHS GWP Global warming potential HET-CAM Hen's Egg Test - Chorionallantoic Membrane HGWP Halocarbon Global Warming Potential

GB (RL)

GB (RL) Page 15 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 07.03.2017 / 0003 Replacing version dated / version: 10.07.2015 / 0002 Valid from: 07.03.2017 PDF print date: 09.03.2017 WD-40®BIKE® Degreaser IARC International Agency for Research on Cancer IATA International Air Transport Association IBC Intermediate Bulk Container International Bulk Chemical (Code) IBC (Code) IC Inhibitory concentration IMDG-code International Maritime Code for Dangerous Goods incl. including, inclusive IUCLIDInternational Uniform ChemicaL Information Database LC lethal concentration LC50 lethal concentration 50 percent kill LCLo lowest published lethal concentration Lethal Dose of a chemical LD LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low LOAELLowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration LOEL Lowest Observed Effect Level LQ Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships n.a. not applicable n.av. not available not checked n.c. n.d.a. no data available NIOSHNational Institute of Occupational Safety and Health (United States of America) NOAEC No Observed Adverse Effective Concentration NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration NOEL No Observed Effect Level ODP Ozone Depletion Potential OECD Organisation for Economic Co-operation and Development org. organic PAH polycyclic aromatic hydrocarbon PBT persistent, bioaccumulative and toxic PC Chemical product category PE Polyethylene PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential ppm parts per million PROC Process category PTFE Polytetrafluorethylene REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the RID International Carriage of Dangerous Goods by Rail) SADT Self-Accelerating Decomposition Temperature SAR Structure Activity Relationship SU Sector of use SVHC Substances of Very High Concern Telephone Tel. ThOD Theoretical oxygen demand TOC Total organic carbon TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances) United Nations Recommendations on the Transport of Dangerous Goods **UN RTDG** VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria)) VOC Volatile organic compounds vPvB very persistent and very bioaccumulative WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK). WHO World Health Organization wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility. These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.