

# MB-Power plug-in connection for round cables SWD4-LR4P, plug 7/8", IP67

Powering Business Worldwide

Part no. SWD4-SF4P-67R Catalog No. 183229

Eaton Catalog No. SWD4-SF4P-67R



## **Delivery program**

Product range	SmartWire-DT accessories
Basic function	Plug/socket
Basic function accessories	Plug-in connection
Function	Plug connector for 4 pole SWD4LR4P round cables
Description	4 pole socket Angled Screw connection
Connection to SmartWire-DT	yes
For use with	EU6E EU8E SWD4LR4P

#### **Technical data**

#### General

Mounting position			As required
Power loss	P	W	0
Note on heat dissipation			not relevant
Ambient conditions, mechanical			
Protection type (IEC/EN 60529, EN50178, VBG 4)			IP67
Climatic environmental conditions			
Climatic proofing			Dry heat to IEC 60068-2-2 Damp heat as per EN 60068-2-3
Air pressure (operation)		hPa	795 - 1080
Ambient temperature			
Operation	9	°C	-25 - +80
Storage / Transport	9	°C	-40 - +80
Relative humidity			
Condensation			permissible

## **Design verification as per IEC/EN 61439**

booign vormounded por 120/211 or 100			
Technical data for design verification			
Static heat dissipation, non-current-dependent	$P_{vs}$	W	0
Heat dissipation capacity	P <sub>diss</sub>	W	0
Operating ambient temperature max.		°C	-25
Operating ambient temperature max.		°C	80
Degree of Protection			IP67
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES			Meets the product standard's requirements.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9 Insulation properties	
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

### **Technical data ETIM 6.0**

PLC's (EG000024) / Accessories for controls (EC002584)		
Electric engineering, automation, process control engineering / Control (accessories) / Control (accessories, unspecified) (ecl@ss8.1-27-24-92-90 [AKN560011])		
Type of electrical accessory	Plug	
Type of mechanical accessory	-	
Type of documentation	-	

# Approvals

North America Certification	UL listed, CSA certified
Specially designed for North America	No

# **Additional product information (links)**

SmartWire-DT product range catalog http://ecat.moeller.ne	t/flip-cat/?edition=SWKAT&startpage=Titel
---	---