

Page 1/10

\*

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.01.2020

Version number 109

Revision: 17.12.2019

SECTION 1:	Identifica	tion of the substance/mixture and of the company/undertaking
1.1 Product iden	tifier	
Trade name: <u>M</u>	OTIP® DEC	CO UNIVERSAL PRIMER GREY/WHITE 400 ML
No further releved Sector of Use SU21 Consume SU22 Professio Product category PROC7 Industr PROC11 Non in	ntified uses of ant informati r uses: Priva mal uses: Pu y PC9a Coo y ial spraying ndustrial spr	of the substance or mixture and uses advised against on available. ate households / general public / consumers blic domain (administration, education, entertainment, services, craftsmen) atings and paints, thinners, paint removers
Manufacturer/S MOTIP DUPLI Wolfraamweg 2 NL- 8471 XC Wo The Netherlands Tel: +31 (0)561 Fax: +31 (0)561 e-mail: msds@n.	upplier: B.V. 694400 694411 l.motipdupli. ttion obtaina celephone nu	<b>ible from:</b> Department Product Safety mber:
UK: NPIS Nation	nal Poisons	Information Centre Tel: +44 0344 892 0111
	Hazards i	dentification
SECTION 2:		
2.1 Classification		stance or mixture Regulation (EC) No 1272/2008
2.1 Classificatio Classification ad		
2.1 Classification	ccording to H	
2.1 Classificatio Classification ac GHS0	2 flame H222-H2	Regulation (EC) No 1272/2008
2.1 Classification Classification ad GHS0 Aerosol 1	2 flame H222-H2	Regulation (EC) No 1272/2008
2.1 Classification Classification ac GHS0 Aerosol 1 GHS0	ccording to <b>I</b> 2 flame H222-H2 7	Regulation (EC) No 1272/2008 29 Extremely flammable aerosol. Pressurised container: May burst if heated.

• Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

(Contd. on page 2) GB Page 2/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.01.2020

Version number 109

Revision: 17.12.2019

# Trade name: MOTIP® DECO UNIVERSAL PRIMER GREY/WHITE 400 ML

	(Contd. of pag
Hazard pi	ctograms
$\wedge$	$\wedge$
$\mathbf{Y}$	
GHS02	GHS07
011002	
· Signal wo	<b>rd</b> Danger
Hazard-d	etermining components of labelling:
acetone	
n-butyl ac	etate
butan-1-o	l
· Hazard st	atements
H222-H22	29 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
· Precautio	nary statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe spray.
P410+P4	12 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents / container in accordance with regional regulations.
Additiona	l information:
	Repeated exposure may cause skin dryness or cracking.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

\*

# **SECTION 3: Composition/information on ingredients**

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	25-<50%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1, H220 Press. Gas (Comp.), H280	10-<12.5%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	10-<12.5%
	((	Contd. on page 3)

Printing date 07.01.2020

Version number 109

Revision: 17.12.2019

## Trade name: MOTIP® DECO UNIVERSAL PRIMER GREY/WHITE 400 ML

	(	Contd. of page 2)
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate � Flam. Liq. 3, H226	5-<10%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane � Flam. Gas 1, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane Flam. Gas 1, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38	<ul> <li>butan-1-ol</li> <li>Flam. Liq. 3, H226</li> <li>Eye Dam. 1, H318</li> <li>Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335- H336</li> </ul>	2.5-<5%
CAS: 9004-70-0	cellulose nitrate 🚸 Flam. Sol. 1, H228	<2.5%
CAS: 7779-90-0 EINECS: 231-944-3 Index number: 030-011-00-6 Reg.nr.: 01-2119485044-40	trizinc bis(orthophosphate) � Aquatic Acute 1, H400; Aquatic Chronic 1, H410	<2.5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

# **SECTION 4: First aid measures**

· 4.1 Description of first aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

×

- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- $\cdot$  4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

#### **SECTION 6:** Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- Wear protective equipment. Keep unprotected persons away.
- $\cdot$  6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

GB

Printing date 07.01.2020

Version number 109

Revision: 17.12.2019

(Contd. of page 3)

## Trade name: MOTIP® DECO UNIVERSAL PRIMER GREY/WHITE 400 ML

- · 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- · 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- Requirements to be met by storerooms and receptacles: Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Not required. • Further information about storage conditions: Keep container tightly sealed.

• Storage class: 2 B

• 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

#### · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

#### 67-64-1 acetone

WEL Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppm Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

### 123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

## 108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m<sup>3</sup>, 100 ppm Long-term value: 274 mg/m<sup>3</sup>, 50 ppm Sk

#### 106-97-8 butane

WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

#### 71-36-3 butan-1-ol

WEL Short-term value: 154 mg/m<sup>3</sup>, 50 ppm Sk

· Additional information: The lists valid during the making were used as basis.

### · 8.2 Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

(Contd. on page 5)

Page 5/10

# Safety data sheet according to 1907/2006/EC, Article 31


Printing date 07.01.2020

Version number 109

Revision: 17.12.2019

GR

## Trade name: MOTIP® DECO UNIVERSAL PRIMER GREY/WHITE 400 ML



Colour:	White	
· Odour:	Solvent-like	
• Odour threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling range:	Not applicable, as aerosol.	
· Flash point:	Not applicable, as aerosol.	
· Flammability (solid, gas):	Not applicable.	
· Ignition temperature:	333 °C (631.4 °F)	
· Decomposition temperature:	Not determined.	
· Explosive properties:	Not determined.	
· Explosion limits:		
Lower:	1.2 Vol %	
		(Contd. on page 6)

Printing date 07.01.2020

Version number 109

Revision: 17.12.2019

GB

## Trade name: MOTIP® DECO UNIVERSAL PRIMER GREY/WHITE 400 ML

	(Contd. of pag	ge 5
Upper:	13 Vol %	
· Vapour pressure at 20 °C (68 °F):	3500 hPa (2625.2 mm Hg)	
• Density at 20 •C (68 •F):	0.8 g/cm <sup>3</sup> (6.7 lbs/gal)	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not applicable.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	86.0 %	
Water:	0.2 %	
VOC (EC)		
	$672.2 \ g/l$	
· VOC-EU%	86.02 %	
· Solids content:	13.5 %	
• 9.2 Other information	No further relevant information available.	

## SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

\*

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.

 $\cdot$  10.4 Conditions to avoid No further relevant information available.

- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## **SECTION 11: Toxicological information**

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:			
67-64-1 ac	etone		
Oral	LD50	5800 mg/kg (rat)	
Dermal	LD50	>15800 mg/kg (rabbit)	
Inhalative	LC50 / 4h	76 mg/l (rat)	
123-86-4 n	n-butyl aceta	ate	
Oral	LD50	10800 mg/kg (rat) (OECD 401)	
Dermal	LD50	>17600 mg/kg (rabbit)	
Inhalative	LC50 / 4 h	>21 mg/m3 (rat)	
108-65-62	-methoxy-1	-methylethyl acetate	
Oral	LD50	8530 mg/kg (rat)	
Dermal	LD50	>5000 mg/kg (rabbit)	
Inhalative	LC50 / 4 h	>10000 mg/m3 (rat)	
		(Contd. on page 2	

Printing date 07.01.2020

Version number 109

Revision: 17.12.2019

## Trade name: MOTIP® DECO UNIVERSAL PRIMER GREY/WHITE 400 ML

		(Contd. of page 6)	
71-36-3 bu	tan-1-ol		
Oral	LD50	2292 mg/kg (rat)	
Dermal	LD50	3430 mg/kg (rabbit)	
Inhalative	LC50 / 4 h	17000 mg/m3 (rat)	

· Primary irritant effect:

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- $\cdot$  Germ cell mutagenicity Based on available data, the classification criteria are not met.
- $\cdot$  Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause drowsiness or dizziness.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

• Aspiration hazard Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

· 12.1 Toxicity

×

· Aquatic toxicity:

67-64-1 acetone

LC50/96h 8300 mg/l (fish)

EC50/96h 7200 mg/l (algae)

LC50 / 48 h 8450 mg/l (crustacean (water flea))

108-65-6 2-methoxy-1-methylethyl acetate

EC50/48 h >500 mg/l (daphnia magna)

LC50 / 96 h 100-180 mg/l (oncorhynchus mykiss / Regenbogenforelle)

71-36-3 butan-1-ol

LC50 / 96 h 1376 mg/l (fish)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

\*

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.01.2020

Version number 109

Revision: 17.12.2019

## Trade name: MOTIP® DECO UNIVERSAL PRIMER GREY/WHITE 400 ML

(Contd. of page 7)

GB

## $\cdot$ European waste catalogue

08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances 15 01 04 metallic packaging

# · Uncleaned packaging:

· Recommendation:

Disposal must be made according to official regulations.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

14.1 UN-Number ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name ADR IMDG IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1
Class	2.1
Label	2.1
14.4 Packing group ADR, IMDG, IATA	not regulated
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user Danger code (Kemler): EMS Number: Stowage Code	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litra Category A. For AEROSOLS with a capacity above 1 litra Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

Printing date 07.01.2020

Version number 109

Revision: 17.12.2019

## Trade name: MOTIP® DECO UNIVERSAL PRIMER GREY/WHITE 400 ML

	(Contd. of page
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre
0.0	Segregation as for class 9. Stow "separated from" class 1
	except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2.
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to A	nnex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	lL
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity
UN ''Model Regulation'':	UN 1950 AEROSOLS, 2.1

# SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P3a FLAMMABLE AEROSOLS

 $\cdot$  Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

 $\cdot$  Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

• REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· National regulations:

· Other regulations, limitations and prohibitive regulations

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H228 Flammable solid.
H280 Contains gas under pressure; may explode if heated.

(Contd. on page 10)

GB

Page 10/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.01.2020

Version number 109

Revision: 17.12.2019

## Trade name: MOTIP® DECO UNIVERSAL PRIMER GREY/WHITE 400 ML

	(Contd. of page 9)
H302 Harmful if swallowed.	
H315 Causes skin irritation.	
H318 Causes serious eye damage.	
H319 Causes serious eye irritation.	
H335 May cause respiratory irritation.	
H336 May cause drowsiness or dizziness.	
H400 Very toxic to aquatic life.	
H410 Very toxic to aquatic life with long lasting effects.	
<b>Department issuing SDS:</b> R&D legislation and regulatory advisor	
Contact: msds@nl.motipdupli.com	
Abbreviations and acronyms:	
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (R	Regulations Concerning the
International Transport of Dangerous Goods by Rail)	
ICAO: International Civil Aviation Organisation	
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement co	oncerning the International
Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
SVHC: Substances of Very High Concern	
vPvB: very Persistent and very Bioaccumulative	
Flam. Gas 1: Flammable gases – Category 1	
Aerosol 1: Aerosols – Category 1	
Press. Gas (Comp.): Gases under pressure – Compressed gas	
Flam. Liq. 2: Flammable liquids – Category 2	
Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3	
Flam. Sol. 1: Flammable solids – Category 1	
Acute Tox. 4: Acute toxicity - oral – Category 4	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Dam. 1: Serious eye damage/eye irritation – Category 1	
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1	
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1	
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	
* Data compared to the previous version altered.	