# HSSE NC machine reamer with uniform shank (fit tolerance and diameter

can be selected) For universal use up to 1000 N/mm<sup>2</sup>

#### Application

for producing fit tolerances in through holes on NC machines or conventional machines up to 1000  $N/mm^2.$ 

### Version

■ 7-8° left-hand spiral, type B

#### Advantage

- Diameter and fit can be ordered to suit, shortest possible delivery time
- high-quality HSSE cutting material for a very long service life
- good bore hole quality (dimensional tolerance, roundness, surface quality)

Application		Steel (N/mm <sup>2</sup> )			Stainless steel		Alu		Brass		Bronze		Plas-				Nickel-		Hard mat.	
		<700	<1000	<1300	marten.	austen.	short	long	short	long	short	long	tics	G(C)FK	GjMW	alloy	alloy	alloy	<55 HRC	<65 HRC
		12	9	7	8	7	17	17	17	17	13	13			11	5	5			

Art. No.	11624 977					
Cutting material	HSSE					
Tolerance of fit	Optional					
Groove type	Left-hand twist, 7-8°					
Tool holding device	HA parallel shank					
Min./max. cutting edge diameter	16.01-16.5 mm					
Length	175 mm					
Cutting edge length	54 mm					
Projecting length	129 mm					
Shaft diameter	14 mm					
Number of cutting edges	8 PCS					
f steel 1300	0.18 mm/r					
DIN	Similar to 212					

## EAN-Code

4050293393774



