

**LK2A****111-60119**

T18S – T150XL



Available in a wide range of materials, these cable ties all feature internal serrations allowing for a positive hold onto cable, hose and pipe bundles. The design of the head guarantees a high tensile strength whilst allowing a very low insertion force, this, combined with the bent tail design of many of the ties ensures a simple and quick installation. Whilst easily installed by hand manual, and pneumatic (for high volume applications) tensioning tools are available to ensure a consistent and safe installation.

For routing, bundling and securing of cables, pipes and hoses.

**Base Data****Colour**

Natural (NA)

**Label E-Number Finland**

13 704 21

**Package Content**

100

**Quantity (Sold Unit / EDP)**

100

**Recommended Application Tool**

MK3SP, MK3PNP2, MK7P, MK7, MK7HT, MK20, MK6, MK6PN, MK9, MK9HT, MK21

**Logisitic and Packaging****Carton Quantity**

6000

**EAN code**

4031026106847

**Quantity of Europallet**

108000

**Weight (kg) (Metric)**

1.1 kg

**Material and Specifications****Flammability**

UL94 V2

**Material**

Polyamide 6.6 (PA66)

**Material Shortcut**

PA66

**Operating Temperature (Metric)**

-40 °C to +85 °C Continuous, (+105 °C for 500 h)

**Product Dimensions****Bundle Diameter max (Metric)**

73

**Bundle Diameter min (Metric)**

5

**Length L (Metric)**

270

**Minimum Tensile Strength (N)**

225

**Width W (Metric)**

4.6