

Blacklight BL368 Linear & Circline

F11W T5 BL368

0000097



Range Features

- Features
- BL368 tubes emit an upgraded highly concentrated radiation with peak around 368 nm. Flying insects eye sensitivity is generally at or near this frequency
- 100% improvement in effectiveness (at 368nm)
- Depreciation of UV-A output over time is significantly reduced (80% at 5000hrs of original 100 hour output)
- Performs longer and better throughout the insect season
- Same shape, structural and electrical characteristics and control circuits as standard T12,T8 or T5 tubes
- Applications
- Insect traps, insect attraction is strongly increased
- Restaurants, kitchens, food shops, supermarkets
- Diazo printing machines
- Photo Polymerisation
- Chemical processing
- Mineral detection
- Various technical applications
- Directions for use
- Maximum exposure limits are set by EN60335-2-59:1997 at an effective 1.0 milliWatt per metre squared (1.0 mW/m²) measured at a distance of 1 metre originally based on the recommendations of the National Radiological Protection Board in the UK. The irradiance value for a single BL368-lamp measured without reflector and/or fixture, in free air at 25 celsius, is varying between 0.2 and 0.4 mW/m² depending on the wattage



PRODUCT OVERVIEW

Lamp finish	Coated
Dimmable	Yes
EAN code	5410288000978
Cap/Base	G5
Type	T5-Special
Watt (Nominal) (W)	11
Ordering number	0000097
Voltage (V)	34

DATA TABLE

General data

Control gear required	Yes
Lamp finish	Coated
Dimmable	Yes

Blacklight BL368 Linear & Circline

F11W T5 BL368

0000097

EAN code	5410288000978
Cap/Base	G5
Type	T5-Special
Ordering number	0000097

Range features

Features
 BL368 tubes emit an upgraded highly concentrated radiation with peak around 368 nm. Flying insects eye sensitivity is generally at or near this frequency
 100% improvement in effectiveness (at 368nm)
 Depreciation of UV-A output over time is significantly reduced (80% at 5000hrs of original 100 hour output)
 Performs longer and better throughout the insect season
 Same shape, structural and electrical characteristics and control circuits as standard T12,T8 or T5 tubes

Applications
 Insect traps, insect attraction is strongly increased
 Restaurants, kitchens, food shops, supermarkets
 Diazo printing machines
 Photo Polymerisation
 Chemical processing
 Mineral detection
 Various technical applications

Directions for use
 Maximum exposure limits are set by EN60335-2-59:1997 at an effective 1.0 milliWatt per metre squared (1.0 mW/m²) measured at a distance of 1 metre originally based on the recommendations of the National Radiological Protection Board in the UK. The irradiance value for a single BL368-lamp measured without reflector and/or fixture, in free air at 25 celsius, is varying between 0.2 and 0.4 mW/m² depending on the wattage

Product name	F11W T5 BL368
Sales pack quantity	25
E-number FI	4940426

Electrical data

Watt (Nominal) (W)	11
Voltage (V)	34

Physical data

Single packaging type	Box/Sleeve
Weight (kg)	0.02

TECHNICAL DRAWINGS

Blacklight BL368 Linear & Circline

F11W T5 BL368

0000097



G5



15,75

