ALPHA FLOW AMF-3CV

P3 DISPOSABLE RESPIRATOR

The Alpha Flow SERIES has been designed to improve comfort and performance whilst maintaining a secure fit. Colour coding the range makes identification simple and easy when varying levels of protection may be required.

FEATURES

- Large surface area ensures very low breathing resistance
- New large exhalation valve which reduces heat build up and improves wearer comfort
- Colour coded alphamesh shell for ease of identification
- Adjustable headstrap allows for a secure and comfortable fit
- Metal-free suitable for food industry applications
- Preformed nosebridge eliminates the need for regular adjustment
- Compatible with a wide range of safety eyewear
- Low profile valve aids field of vision and reduces build-up of heat/moisture
- Conforms to EN 149:2001+A1:2009

ORDERING INFORMATION

Part Number: AMF-3CV

Packaging:	10 singles per box
	10 boxes per case

Certification: EN149: 2001 + A1 2009





NEW LARGE EXHALATION VALVE

N 149:20 FED3 ND



NEW MESH

DESIGN

SUITABLE APPLICATIONS

Recommended applications include:

- **Craft Work**
- **Cutting and Casting of** Metals
- **Disposal of Toxic Waste**
- Hospital
- Iron and Steel Industry Laboratory and Disease
 - Control
- **Manufacture of Batteries** Mining
- **Pharmaceutical industry Textile industry**
- **Underground Civil**
- Engineering
- Woodworking Welding work





LPHA FLOW AMF-3CV

P3 DISPOSABLE RESPIRATOR

TECHNICAL SPECIFICATIONS

MATERIALS

COMPONENT	MATERIAL			
Mesh Shell:	Polypropylene			
Filter Outer Layer:	Polypropylene			
Filter Inner Layer:	Polypropylene			
Filter Internal Media:	Melt-Blown [Polypropylene]			
Headstrap:	Woven Elastic [Latex-Free] Rubber			
Headstrap Adjuster:	Polypropylene			
Exhalation Valve - Valve Housing:	Polypropylene & ABS			
Valve Membrane:	Synthetic Rubber			
CV Pre-filter:	Activated Carbon Loaded Polypropylene			

DIMENSIONS

ITEM	LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)	
Respirator	155	70	125	
Nosebridge	25	50	35	
Headband	700	9	0.4	
Headband clip	57	12	9	
Valve	43	43	10	

CERTIFICATION

EC-Type Examination Certification according to European Council Directive 89/686/EEC and subsequent amendments, certified by BSI, Kitemark House, Maylands Ave, Hemel Hempstead HP2 4SQ.

Notified Body: INSPEC International Ltd., 56 Leslie Hough Way, Salford, Greater Manchester, M6 6AJ, UK. [N.B. No. 0194]

RECOMMENDATIONS FOR USE

This respirator is disposable and recommended for single use only.

Do not attempt to clean or re-use.

PRODUCT SELECTOR GUIDANCE CHART

Approval EN 149:2001 + A1:2009	Mesh Colour	Product Codes	APF (Assigned Protection Factor) (x WEL)	Non-Toxic Dusts	Fine / Toxic Dusts / Mists / Fumes	VeryFine / Toxic Dusts / Mists / Fumes	Odours/ Organic Vapours (Below WEL)	Metal Fumes	Oil/Water Based Particulates
FFP1 NR	White	AMF-1	4						
FFP2 NR	Blue	AMF-2	10	0				0	
FFP2 NR	Blue	AMF-2V	10	0				0	
FFP3 R D 🖌	Orange	AMF-3V	20	0				0	
FFP3 NR 🖌	Grey	AMF-3CV	20	0					

Recommended O = Alternative A = Full Inner Face Seal

www.alphasolway.com T: +44 (0)1461 202452 E: sales@alphasolway.com



ALPHA SOLWAY LTD, Factory 1, Queensberry Street, Annan, DG12 5BL, UK

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary. © 2016 Alpha Solway Ltd | ALPHA-DATA-AMF-3CV-1016