HSSE NC machine reamer with uniform shank (fit tolerance and diameter can be selected)



For universal use up to 1000 N/mm²

Application

for producing fit tolerances in through holes on NC machines or conventional machines up to 1000 $\mbox{N/mm}^2.$

Version

■ 7-8° left-hand spiral, type B

Advantage

- Diameter and fit can be ordered to suit, shortest possible delivery time
- high-quality HSSE cutting material for a very long service life
- good bore hole quality (dimensional tolerance, roundness, surface quality)

Application	cation Steel (N/mm²)			Stainless steel		Alu		Brass				Plas-		GG(G)	Titan-			Hard mat.	
	<700	<1000	<1300	marten.	austen.	short	long	short	long	short	long	tics	G(C)FK	GjMW	alloy	alloy	alloy	<55 HRC	<65 HRC
	12	9	7	8	7	17	17	17	17	13	13			11	5	5			

Art. No.	11624 919				
Cutting material	HSSE				
Tolerance of fit	Optional				
Groove type	Left-hand twist, 7-8°				
Tool holding device	HA parallel shank				
Min./max. cutting edge diameter	2.81-3 mm				
Length	61 mm				
Cutting edge length	15 mm				
Projecting length	30 mm				
Shaft diameter	3 mm				
Number of cutting edges	6 PCS				
f steel 1300	0.12 mm/r				
DIN	Similar to 212				

EAN-Code

4050293393484

