

PE TERMINAL 2 SCREW TERMINALS GREEN-YELLOW, 8MM, SZ 6



Figure similar

General technical data		
Insulation material		thermoplastic
Terminal contact spacing	mm	8
Protection class		
Combustibility class acc. to UL 94		V2
Appearance		
Color		green-yellow
Product details		
Product feature / PEN function		No
Product component / required / connection plate		No
Number		
Number of terminal levels		2
Number of terminal points / per terminal level		1
Connections		
Connectable conductor cross-section / stranded		
• maximum	mm ²	6
Connectable conductor cross-section		
• solid		
— maximum	mm ²	6
• finely stranded		
— with core end processing / maximum	mm ²	6
— without core end processing / maximum	mm ²	6
Type of electrical connection		

• 1		screw-type terminal
• 2		screw-type terminal
Position / of the terminal		lateral

Mechanical Design

Height / with lowest-profile installation	mm	33
Length	mm	51
Mounting type		DIN rail 35 mm

Environmental conditions

Ambient temperature		
• during operation / minimum	°C	-25
• during operation / maximum	°C	55

General Product Approval	Test Certificates	Shipping Approval
--------------------------	-------------------	-------------------



[other](#)



Shipping Approval	other
-------------------	-------



[Environmental Confirmations](#)

[other](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WA10111PH00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WA10111PH00/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA10111PH00

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

11.03.2015