Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Hera GmbH & Co KG

Supplier's address: FE, Dieselstraße 9, 32130 Enger Herford, DE

Model identifier: SR 68-LED 4.8W

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type	nein		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	Nein
Colour-tuneable light source:	Nein	Envelope:	-
High luminance light source:	Nein		
Anti-glare shield:	Nein	Dimmable:	Only with specific dimmers

Product parameters

Parameter		Value	Parameter	Value			
General product parameters:							
Energy consump mode (kWh/1000 up to the nearest) h), rounded	5	Energy efficiency class	E			
Useful luminous indicating if it refe in a sphere (360 cone (120º) or in a (90º)	ers to the flux º), in a wide	485 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700 or 3 000 or 4 000			
On-mode pov expressed in W	wer (P _{on}),	4,8	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00			
Networked standb for CLS, expresse rounded to the se	ed in W and	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	90			
Outer H	leight	80	Spectral power	See image			
dimensions V	Width	80	distribution in the	in last page			

separate control gear, lighting control parts and non- lighting control parts, if any	Depth	36	range 250 nm to 800 nm, at full-load	
(millimetre) Claim of equivale	nt power ^(a)	-	If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	0,435 0,407
Parameters for di	irectional light s	ources:		
Peak luminous int	tensity (cd)	1	Beam angle in degrees, or the range of beam angles that can be set	30
Parameters for LE	ED and OLED lig	ht sources:	1	
R9 colour renderi	ng index value	0	Survival factor	0,00
the lumen mainte	enance factor	0,00		
(a), , not applicable.			·	

(a)_{'-'} : not applicable;

(b)'-' : not applicable;

