



PRODUKTINFORMATION

Vi reserverar oss mot fel samt förbehåller oss rätten till ändringar utan föregående meddelande

ELFA artikelnr

54-106-00 Fläkt DC 412F 40x40

54-106-34 Fläkt DC 412 40x40

54-106-59 Fläkt DC 405F 40x40



- DC fans with electronically commutated external rotor motor. Fully integrated commutation electronics.
- With electronic protection against reverse polarity. The fan only operates when the polarity is correct. Impedance-protected* against blocking and overloading.

- Fan of fibreglass reinforced plastic. PBT housing, PA impeller.
- Air exhaust over struts. Rotational direction CCW looking at rotor.
- Electrical connection via 2 leads AWG 28, TR 64. Stripped and tinned ends.
- Mass 17 g (27 g).

Series 400F

40 x 40 x 10 mm

Air flow		Nominal Voltage	Voltage Range	Noise	Sinter-Sleeve Bearings		Power Input	Nominal Speed	Temperature Range	Service Life L ₁₀		Curve	Type	Specials
m ³ /h	CFM				V DC	V DC				bels	□/■			
8	4.7	5	4.5...5.5	26	4.5	□	0.7	5400	-20...+70	45 000/15 000		2	405 F	58
9	5.3	5	4.5...5.5	29	4.9	□	0.9	6000	-20...+70	45 000/15 000		3	405 FH	
6	3.5	12	10...14	19	4.0	□	0.6	4300	-20...+70	45 000/15 000		1	412 FM	
8	4.7	12	10...14	26	4.5	□	0.7	5400	-20...+70	45 000/15 000		2	412 F	
9	5.3	12	10...14	29	4.9	□	0.8	6000	-20...+70	45 000/15 000		3	412 FH	58
8	4.7	24	20...28	26	4.5	□	0.8	5400	-20...+70	45 000/15 000		2	414 F	

Series 400

40 x 40 x 20 mm

10	5.9	5	4.5...5.5	18	3.8	□	0.9	6000	-20...+70	50 000/20 000		4	405	58
10	5.9	12	10...14	18	3.8	□	1.0	6000	-20...+70	50 000/20 000		4	412	58
13.5	8.0	12	10...14	29	3.8	□	1.6	8100	-20...+60	45 000/15 000		5	412 H	
10	5.9	24	20...28	18	3.8	□	1.0	6000	-20...+70	50 000/20 000		4	414	58
13.5	8.0	24	20...26.5	29	4.7	□	1.6	8100	-20...+60	45 000/15 000		5	414 H	58

*Type 412 H and 414 H with electronic protection against blocking

Type	Dimension:	A	B	C
400F		10 ^{+0.3} _{-0.1}	Ø3.5 ±0.1	Ø3.5 ±0.1
400		20 ±0.15	Ø4.3 ±0.1	Ø4.3 ±0.1

