Solid carbide HSC single-tooth milling cutter

1 cutter, uncoated

Application

For the milling, grooving and contour milling of standard plastics.

Version

- Solid carbide ultra-fine grain
- Straight shank in line with DIN 6535 HA
- Uncoated
- Surface polished
- With centre cutting
- For soft standard plastics like thermoplastics PVC, PE, PP, etc.
- UpCut

Advantage

- Ideal for sheet metal, boards and thin-walled materials
- Large chip space for easy chip removal

4	Application	ation Steel (N/mm ²)		Stainless steel		Alu		Brass		Bronze		Plas-			Titan-			Hard mat.		
		<700	<1000	<1300	marten.	austen.	short	long	short	long	short	long	tics	G(C)FK	GjMW	alloy	alloy	alloy	<55 HRC	<65 HRC
													345							

Art. No.	16656 610					
Cutting material	VHM					
Surface	Uncoated					
Туре	Right-hand twist					
Number of cutting edges	1 PCS					
Twist angle	30°					
Tool holding device	HA parallel shank					
Overall length	Normal					
Cutting edge diameter	3 mm					
Cutting edge length	12 mm					
Length	64 mm					
Shaft diameter	3 mm					
fz aluminium	0.15 mm					
Overall stainless steel suitability	3					
fitness not iron total	3					
fitness Titan/Nickel/Super total	3					

EAN-Code

4050293435337



TORN®

