

# Thompson's®

## SAFETY DATA SHEET THOMPSON'S EMERGENCY LEAK FIX

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name THOMPSON'S EMERGENCY LEAK FIX

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Sealant.

#### 1.3. Details of the supplier of the safety data sheet

Supplier Ronseal Ltd  
Thornccliffe Park  
Chapelton  
Sheffield  
S35 2YP  
+44 (0) 114 246 7171  
enquiry@ronseal.co.uk  
sds@ronseal.co.uk

Contact Person sds@ronseal.co.uk

#### 1.4. Emergency telephone number

Tel +44 (0) 114 246 7171 (office hours only)

Fax +44 (0) 114 245 5629

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

Classification (1999/45/EEC) R10, R66, R67.

#### 2.2. Label elements

##### Risk Phrases

R10 Flammable.  
R66 Repeated exposure may cause skin dryness or cracking.  
R67 Vapours may cause drowsiness and dizziness.

##### Safety Phrases

S2 Keep out of the reach of children.  
S24/25 Avoid contact with skin and eyes.  
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S37 Wear suitable gloves.  
S46 If swallowed, seek medical advice immediately and show this container or label.  
S51 Use only in well-ventilated areas.

#### 2.3. Other hazards

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.2. Mixtures

# THOMPSON'S EMERGENCY LEAK FIX

<b>BUTYL ACETATE -norm</b>		<b>25-50%</b>
CAS-No.: 123-86-4	EC No.: 204-658-1	
Classification (EC 1272/2008)	Classification (67/548/EEC)	
Flam. Liq. 3 - H226	R10	
EUH066	R66	
STOT SE 3 - H336	R67	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

#### Inhalation

Remove to fresh air, keep the patient warm and at rest. If breathing has stopped administer artificial respiration. Give nothing by mouth. If unconscious, place in the recovery position and seek medical advice.

#### Ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

#### Skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water, or use a recognised skin cleanser. Do NOT use solvents or thinners. Seek medical advice if any irritation persists.

#### Eye contact

Contact lenses should be removed. Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

### 4.2. Most important symptoms and effects, both acute and delayed

### 4.3. Indication of any immediate medical attention and special treatment needed

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

#### Extinguishing media

Fire can be extinguished using: recommended: alcohol resistant foam, carbon dioxide (CO<sub>2</sub>), powders, water spray/ mist. Not to be used for safety reasons: water jet.

### 5.2. Special hazards arising from the substance or mixture

### 5.3. Advice for firefighters

#### Special Fire Fighting Procedures

Fire will produce dense black smoke containing hazardous products of combustion (see Section 10). Exposure to decomposition products may be hazardous to health. Appropriate self-contained breathing apparatus may be required. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or watercourses.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

### 6.2. Environmental precautions

### 6.3. Methods and material for containment and cleaning up

Exclude sources of ignition and ventilate the area. Exclude non-essential personnel. Avoid breathing vapours. Refer to protective measures listed in Section 7 and 8. Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth or vermiculite, and place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Clean preferably with a detergent; avoid the use of solvents. If the product enters drains or sewers, immediately contact the local water company; in the case of contamination of streams, rivers or lakes, the relevant environment agency.

### 6.4. Reference to other sections

# THOMPSON'S EMERGENCY LEAK FIX

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupational exposure limits. Container must be kept tightly closed. Keep away from heat, sparks and open flame. Smoking, eating and drinking should be prohibited in application area. Avoid skin and eye contact. Avoid inhalation of vapour.

For personal protection, refer to Section 8.

The Manual Handling Operations Regulations may apply to the handling of containers/packages of this product. Refer to the guide weight indicated on the container when carrying out assessments.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed. Observe the label precautions. Store between 5°C and 25°C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep in a cool, dry, well ventilated place, away from sources of heat, ignition and direct sunlight. No smoking.

The principles contained in the HSE Guidance Note: Storage of Packaged Dangerous Substances, should be observed when storing this product.

To avoid the risk of spillage, always store and transport in a secure and upright position.

### 7.3. Specific end use(s)

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
BUTYL ACETATE -norm	WEL	150 ppm	724 mg/m <sup>3</sup>	200 ppm	966 mg/m <sup>3</sup>	

WEL = Workplace Exposure Limit.

#### Ingredient Comments

WEL = Workplace Exposure Limits

### 8.2. Exposure controls

#### Engineering measures

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and/or solvent vapours below the relevant occupational exposure limits, suitable respiratory protective equipment should be worn.

#### Respiratory equipment

If exposure to hazardous substances identified above cannot be controlled by the provision of local exhaust ventilation and good general extraction, suitable respiratory protective equipment should be worn.

#### Hand protection

When skin exposure may occur, advice should be sought from glove suppliers on appropriate types. Barrier creams may help to protect exposed areas of skin but are not substitutes for full physical protection. They should not be applied once exposure has occurred.

#### Eye protection

Eye protection designed to protect against liquid splashes should be worn.

#### Other Protection

Cotton or cotton/synthetic overalls or coveralls are normally suitable. Grossly contaminated clothing should be removed and the skin washed with soap and water or a proprietary skin cleaner. Do not use solvents or thinners as skin cleaning agents.

All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH Regulations.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance	Very high viscosity liquid/paste.
Colour	Almost colourless.
Odour	Characteristic sweet odour.
Solubility	Immiscible with water
Initial boiling point and boiling range	> 125 760 mm Hg

# THOMPSON'S EMERGENCY LEAK FIX

Flash point ~25 CC (Closed cup).

## 9.2. Other information

### SECTION 10: STABILITY AND REACTIVITY

#### 10.1. Reactivity

#### 10.2. Chemical stability

Stable if stored under recommended storage and handling conditions (see section 7).

#### 10.3. Possibility of hazardous reactions

#### 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition.

#### 10.5. Incompatible materials

#### 10.6. Hazardous decomposition products

In a fire, hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide and oxides of nitrogen may be produced.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1. Information on toxicological effects

##### **Toxicological information**

There is no data available on the product itself. The product has been assessed following the conventional method in CHIP and is classified for toxicological hazards accordingly. This takes into account, where known, delayed and immediate effects and also chronic effects from components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. See Sections 2 and 15 for details of the resulting hazard classification.

Exposure to organic solvent vapours in excess of the stated occupational exposure limit may result in adverse health effects such as irritation of the mucous membrane and the respiratory system and adverse effects on the kidney, liver and central nervous systems. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin.

Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Splashes in the eyes may cause irritation and reversible local damage.

### SECTION 12: ECOLOGICAL INFORMATION

##### **Ecotoxicity**

The product has been assessed following the conventional method in CHIP and is not classified as dangerous for the environment.

#### 12.1. Toxicity

##### **Acute Fish Toxicity**

There is no data available on the mixture itself.

#### 12.2. Persistence and degradability

##### **Degradability**

There is no data available on the product itself.

#### 12.3. Bioaccumulative potential

#### 12.4. Mobility in soil

#### 12.5. Results of PBT and vPvB assessment

# THOMPSON'S EMERGENCY LEAK FIX

## 12.6. Other adverse effects

### SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1. Waste treatment methods

Do not allow into drains or watercourses, or dispose of where ground or surface waters may be affected. Wastes and emptied containers are controlled wastes and should be disposed of in accordance with The Environmental Protection (Duty of Care) Regulations (in England, Scotland & Wales) or The Controlled Waste (Duty of Care) Regulations in Northern Ireland. Using information provided in this data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

### SECTION 14: TRANSPORT INFORMATION

#### General

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in an accident or spillage.

Limited Quantity concessions may apply to the carriage of this product.

#### Road Transport Notes

In pack sizes up to 450 litres, under the terms of 2.2.3.1.5, this product is not subject to the provisions of ADR.

#### Sea Transport Notes

Transport in accordance with 2.3.2.5 of the IMDG Code.

#### 14.1. UN number

UN No. (ADR/RID/ADN) 1133

UN No. (IMDG) 1133

#### 14.2. UN proper shipping name

Proper Shipping Name ADHESIVES containing flammable liquid.

#### 14.3. Transport hazard class(es)

ADR/RID/ADN Class 3

IMDG Class 3

#### Transport Labels



#### 14.4. Packing group

ADR/RID/ADN Packing group III

IMDG Packing group III

#### 14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant  
No.

#### 14.6. Special precautions for user

EMS F-E; S-D

Tunnel Restriction Code (D/E)

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

### SECTION 15: REGULATORY INFORMATION

# THOMPSON'S EMERGENCY LEAK FIX

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **Uk Regulatory References**

This information contained in this data sheet is provided in accordance with the requirements of The Chemicals (Hazard Information and Packaging for Supply) Regulations [CHIP].

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks as required by other health and safety legislation. The provisions of the Health and Safety at Work etc. Act and the Control of Substances Hazardous to Health Regulations apply to the use of this product at work.

The Manual Handling Operations Regulations

The Chemicals (Hazard Information and Packaging for Supply) Regulations.  
The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations.

European Agreement concerning the International Carriage of Dangerous Goods by Road [ADR]

### **Guidance Notes**

Workplace Exposure Limits EH40.

### **EU Legislation**

Dangerous Preparations Directive 88/379. Safety Data Sheet Directive 91/155 Dangerous Substance Directive 67/548

### **Water hazard classification**

There is no data available on the product itself. The product should not be allowed to enter drains or watercourses, or be deposited where it can affect ground or surface waters.

## 15.2. Chemical Safety Assessment

## SECTION 16: OTHER INFORMATION

### **General information**

The information contained in this safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

The product should not be used for purposes other than those shown in section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

For specific guidance contact Ronseal Technical Services. [Helpline +44 (0) 114 240 9469 ] ; Email: enquiry@ronseal.co.uk

**SDS No.** 10137/4

**Safety Data Sheet Status** Approved.

**Date** 22-10-2011

### **Risk Phrases In Full**

R10 Flammable.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

### **Hazard Statements In Full**

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

### Disclaimer

Information contained in this Safety Data Sheet is based on data considered to be accurate at the time of its preparation. Despite our efforts, it may not be up to date or applicable to the circumstances of any particular case. ,

The supplier accepts no responsibility whatsoever (except otherwise provided in law) for any damage or injury resulting from abnormal use, from any failure to follow appropriate practices or from hazards inherent in the product.