TECHNICAL DATA SHEET



Microphone Cable Model: 670BLK

RoHS Compliant

Design of cable:	
Inner conductor	7/0.20±0.004 strand bare copper Ø0.06±0.1mm
Insulation	PVC
Insulation Dia	Ø1.0±0.1mm
Colour	Red/Blue
Screening	58/0.10±0.003mm bare copper
Jacket	Soft PVC
Colour	Black
Size	Ø3.2±0.2mm
Wall thickness	≈0.8mm
Printing	By request
Electric data at 20°C	
Conductor resistance	≤96.0Ω/km
Insulation resistance	≥200MΩ*km
Testing voltage	wire/wire/screen 50Hz1min=800V
Other requirements	
Permissible temperature	-10°C60°C
Packing	100M on non-returnable reel

Important Notice: This data sheet and its contents (the "Information") belong to pro-POWER. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but pro-POWER assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where pro-POWER was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict pro-POWER's liability for death or personal injury resulting from its negligence.

