

SERVICE SET FOR TP 177MICRO, TP 177A, TP 177B, OP 177B  
 AMOUNT AND CONTENT: SEE TECHNICAL DATA



<b>Product type designation</b>	
<b>Standards, approvals, certificates</b>	
CE mark	Yes
<b>Ambient conditions</b>	
<b>Ambient temperature in operation</b>	
• Min.	0 °C
• max.	55 °C
<b>Storage/transport temperature</b>	
• Min.	-20 °C
• max.	70 °C
<b>Relative humidity</b>	
• Operation, max.	95 %
<b>Scope of supply</b>	
Number of sets	1; Content: 1 x mounting seal TP 177, 1 x mounting seal OP 177, 7 x plastic mounting clip, 1 x 2-pin female connector
<b>other</b>	
Note:	for TP 177micro, TP 177A, TP 177B, OP 177B
<b>Usable in the following products</b>	
• Product 1	<a href="#">6AV6640-OCA11-0AX0</a>
• Product 2	<a href="#">6AV6642-OAA11-0AX0</a>
• Product 3	<a href="#">6AV6642-OAA11-0AX1</a>
• Product 4	<a href="#">6AV6642-0BC01-1AX0</a>
• Product 5	<a href="#">6AV6642-0BA01-1AX0</a>

- Product 6
- Product 7
- Product 8
- Product 9
- Product 10
- Product 11
- Product 12
- Product 13

**last modified:**

[6AV6642-0BD01-3AX0](#)

[6AV6642-0BA01-1AX1](#)

[6AV6642-0BC01-1AX1](#)

[6AV6642-8BA10-0AA0](#)

[6AV6642-0DC01-1AX0](#)

[6AV6642-0DA01-1AX0](#)

[6AV6642-0DC01-1AX1](#)

[6AV6642-0DA01-1AX1](#)

12.03.2015