HSSE NC machine reamer with uniform shank (fit tolerance and diameter can be selected)



For universal use up to 1000 N/mm²

Application

for producing fit tolerances in through holes on NC machines or conventional machines up to 1000 $\mbox{N/mm}^2.$

Version

■ 7-8° left-hand spiral, type B

Advantage

- Diameter and fit can be ordered to suit, shortest possible delivery time
- high-quality HSSE cutting material for a very long service life
- good bore hole quality (dimensional tolerance, roundness, surface quality)

	Application	Steel (N/mm²)		Stainless steel		Alu		Brass				Plas-						Hard mat.		
		<700	<1000	<1300	marten.	austen.	short	long	short	long	short	long	tics	G(C)FK	GjMW	alloy	alloy	alloy	<55 HRC	<65 HRC
ĺ		12	9	7	8	7	17	17	17	17	13	13			11	5	5			

Art. No.	11624 993					
Cutting material	HSSE					
Tolerance of fit	Optional					
Groove type	Left-hand twist, 7-8°					
Tool holding device	HA parallel shank					
Min./max. cutting edge diameter	1.51-1.7 mm					
Length	43 mm					
Cutting edge length	9 mm					
Projecting length	23 mm					
Shaft diameter	2 mm					
Number of cutting edges	3 PCS					
f steel 1300	0.12 mm/r					
DIN	Similar to 212					

EAN-Code

4050293393866

