# STREAM<sup>™</sup> (RED)



A lightweight sports-style safety spectacle featuring an adjustable rubber nose bridge to allow a secure fit for the majority of users. The robust wraparound lens complements the extremely flexible side arms to result in stylish, metal-free, frameless eyewear with a wide field of vision.

## **SPECIAL FEATURES**

- Single wraparound polycarbonate lens
- Soft, adjustable, anti-slip nose bridge
- Flexible temple tips
- Co-injected bi-colour thermoplastic rubber temples provide a secure fit
- Slim temples enhance comfort when worn with ear defenders
- Lateral protection
- 100% metal free
- Supplied with a microfibre storage pouch
- Weight: 23g
- 9.5-Base lens













VERSIONS	REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
CLEAR	RLY00201	2C-1.2 € 1FTKN C €	<b>e</b> EN 166 FT <b>C €</b>	Impacts, UV radiations	
GREY	) RLY00202	5-2.5 <b>€</b> 1FTKN <b>C €</b>	<b>€</b> EN 166 FT <b>C €</b>	Impacts, UV and Solar radiations	7 FL. 10 N 2 100 7 110 100 7
AMBER	RLY00204	2C-1.2 € 1FTKN C €	<b>€</b> EN 166 FT <b>C €</b>	Impacts, UV radiations	Moisture repellent
INDOOR/OUTDOOR	) RLY00203	5-1.7 <b>€</b> 1FT <b>C €</b>	<b>€</b> EN 166 FT <b>C €</b>	Impacts, UV radiations	Riley Translucent Mirror Coating. Moisture Repellent + Anti-fog on inside
STREAM FOAM INSER	RLYA0013	n/a	n/a	n/a	n/a

See overleaf for this product's technical specification ....>



## STREAM™ (RED)



#### **GENERAL SPECIFICATION**

LENS BASE	9.5mm
WEIGHT	23g

#### **PACKAGING**

Individually contained in a polythene bag with a Euroslot

PER BOX	10
PER CARTON	200

#### **COMPONENT SPECIFICATION**

COMPONENT MATERIAL		FEATURES
LENS	Polycarbonate	One piece moulded lens with side protection
NOSE BRIDGE	Thermoplastic Elastomers (TPE)	Comfortable and flexible
TEMPLE	TR90 Thermoplastic / Thermoplastic Elastomers (TPE)	Co-injected - Robust, flexible, lightweight and ventilated
HINGE TR90 Thermoplastic		Metal free and durable

#### **LENS MARKINGS**

#### LENS FILTER TYPE:

 $\mathbf{2C} \ \cup \forall$ 

**5** Solar

## SCALE NUMBER (SHADE):

1.2 Clear or Amber

1.7 Minimises or I/O

**2.5** Grev

@ Riley identity

#### **OPTICAL CLASS:**

1 High optical quality

## MECHANICAL STRENGTH:

F Low energy impact, resists a 6mm, 0.86g ball at 45m/s

T Protection against high-speed particles at extreme temperatures

## PERFORMANCE:

K Resistance to scratches by fine particles

N Resistance to fogging

C€ Certification mark

#### **FRAME MARKINGS**

@ Identity of manufacturer

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

## MECHANICAL STRENGTH:

F Low energy impact, resists a 6mm, 0.86 g ball at 45m/s

T Protection against high-speed particles at extreme temperatures

C€ Certification mark

#### **CLEANING AND STORAGE**

**CLEANING:** The lenses should be cleaned regularly.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the

complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

## PART OF THE GLOBUS GROUP

Based on a substantial heritage of successfully protecting hands, Globus has grown to become one of the world leaders in worker safety, leading the way in technical innovation to provide a range of products that have set the standard for safety, productivity and wearer acceptance.

This focus on creating cutting edge personal protection solutions has now extended to eye and face protection with Riley; a new collection of high performance protective eyewear products engineered with innovation and ingenuity, designed for optimum comfort and styled for safe working.

Riley product approval certificates to CE standards will be provided on request. Riley is a registered trademark.

## www.riley-eyewear.com

E: info@riley-eyewear.com

T: +44 (0)161 877 4747

F: +44( 0)161 877 4746

Globus (Shetland) Ltd, 14 Central Park, Mosley Road, Manchester, M17 1NY, UNITED KINGDOM

