# NC machine reamer HSSE with straight shank For universal use up to 1000 $\mbox{N/mm}^{2}$



## Application

for cutting H7 fit tolerances in through holes and blind holes on NC machines or conventional machines up to 1000  $\rm N/mm^2.$ 

 $\blacksquare$  7-8  $^{\circ}$  left-hand spiral, type B, with centring points on both sides and continuous shank

■ good bore hole quality (dimensional tolerance, roundness, surface quality)

Application	oplication Steel (N/mm²)			Stainless steel		Alu		Brass					Graphite					Hard mat.	
	<700	<1000	<1300	marten.	austen.	short	long	short	long	short	long	tics	G(C)FK	GjMW	alloy	alloy	alloy	<55 HRC	<65 HRC
	12	9	7	8	7	17	17	17	17	13	13	13		11	5	5	5		

Art. No.	11628 013
Cutting material	HSSE
Tolerance of fit	H7
Groove type	Left-hand twist, 7-8°
Tool holding device	HA parallel shank
Cutting edge diameter	1.3 mm
Length	38 mm
Cutting edge length	8 mm
Projecting length	16.5 mm
Shaft diameter	1 mm
Number of cutting edges	3 PCS
Surface	Uncoated
f steel 1000	0.1 mm/U
DIN	212

### **EAN-Code**

4050293008876

