## Bits for TORX® Screws







BITORSION





**EAN/GTIN:** 4013288099792 **Dimension:** 

Part no.:05134376001Weight:8 gArticle no.:867/1 BDC SB TX20Country of origin:CZ

Customs tariff 82079030

number:

- For recessed TORX® screws
- BiTorsion zone to absorb peak loads
- Diamond coating for a secure fit in the screw, literally bites into the screwhead to prevent cam-out
- 1/4" hexagon drive
- "Take it easy" Tool Finder: colour coding according to profile and size

## Weblink

 $http://products.wera.de/en/bits\_holders\_adaptors\_the\_range\_of\_wera\_bits\_bits\_for\_torx\_screws\_867\_1\_bdc\_sb\_sis.html$ 

Wera - 867/1 BDC SB TX20 05134376001 - 4013288099792 100x60x10 mm

# 867/1 BDC SB TORX® bits, TX 20 x 25 mm

Bits for TORX® Screws



Bits for recessed TORX® screws with tiny diamond particles on the bit tip. This ensures a secure fit of the bit in the screw, reduces the contact pressure required and lowers the risk of slipping. Come with a Torsion zone — where kinetic energy is diverted from peak loads — and softer BiTorsion zone to prevent the bit tip from twisting under peak loads. This greatly extends the product service life. ¼" hexagon, suitable for holders as per DIN ISO 1173-D 6.3.

#### Bits for TORX® Screws



## Content:



Particularly

at lower cost.

when

involve sensitive materials or high

quality surfaces are involved, bits

with a diamond coating ensure

that work is done safer, faster and

applications

## 867/1 TORX® BDC

05066104001 1 x TX 20x25

# N Wera

## **BiTorsion Bits**



Peak forces that occur in power tool applications often result in premature wear of bits or damage to the screw head. This usually occurs during initial power-up and the when the screw comes to a standstill. Screwdriving could become more productive and safer if these peak loads could be minimised. The Wera BiTorsion system prevents premature wear. The service life of the tool is

extended and the productivity of


tool

significantly increased.

power

applications

## Above-average service life



Even the service life of conventional bits is enhanced with the use of the BiTorsion holder and the BiTorsion bit also functions in a normal holder.

## **Diamond-coated Bits**




One of the greatest problems with power tool applications is that the conventional bit easily slips out of the head of the screw (cam-out). This often destroys both the head of the screw and the tool. High resulting costs are incurred e.g. from damaged surfaces and screw connections that can no longer be loosened. Screwdriving will become safer and more economic if this problem of slipping can be minimised.

## Weblink

#### Bits for TORX® Screws



## Secure fit in the screw head




Today, the Wera diamond bit — manufactured with the technology specifically developed by Wera for this application — still sets the standard in terms of resilience and functionality. Wera bits with a diamond coating ensure a secure fit of the bit in the screw head.

## Reduced cam-out forces




The minute diamond particles applied to the tip of the tool literally "bite" into the screw and ensure an exact, anti-slip fit in the head of the screw. This secure fit protects the screw. The cam-out forces which compel the user to apply greater pressure to the screw are considerably reduced.

## Perfect fit



Ideal for sensitive materials

## "Take it easy" tool finder



"Take it easy" tool finder with colour coding according to profiles and size stamp – for simple and rapid accessing of the required tool.