
## Rotary actuator DSM-6-90-P-A Part number: 173195

**FESTO** 





## **Data sheet**

| Feature                                  | Value  |
|--|--|
| Size                                     | 6  |
| Cushioning angle                         | 0.5 deg  |
| Swivel angle                             | 0 deg 90 deg   |
| Type code                                | DSM  |
| Cushioning                               | Elastic cushioning rings/pads at both ends                         |
| Mounting position                        | Any  |
| Mode of operation                        | Double-acting  |
| Design                                   | Rotary vane  |
| Position sensing                         | For proximity sensor   |
| Symbol                                   | 00991265   |
| Operating pressure                       | 3.5 bar 8 bar  |
| Max. swivel frequency at 6 bar           | 3 Hz   |
| Operating medium                         | Compressed air as per ISO 8573-1:2010 [7:4:4]                      |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Ambient temperature                      | 0 °C 60 °C   |
| Theoretical torque at 6 bar              | 0.15 Nm  |
| Permissible mass moment of inertia       | 6.5E-4 kgm²  |
| Product weight                           | 50 g   |
| Type of mounting                         | With internal thread   |
| Pneumatic connection                     | M3   |
| Note on materials                        | Free of copper and PTFE<br>RoHS-compliant                          |
| Drive shaft material                     | High-alloy stainless steel   |
| Seals material                           | TPE-U(PU)  |
| Housing material                         | Aluminum<br>Anodized   |