SIEMENS

Data sheet 6GT2800-4BB00

product type designation



RF340T transponder

SIMATIC RF300 Transponder RF340T 8 KB FRAM, IP67/X9K, -25 to +85 °C, 48x2 5x 15 mm, minimum order quantity 5 units.

| suitability for operation | RF300 | |
|--|--|--|
| radio frequencies | | |
| operating frequency / rated value | 13.56 MHz | |
| range / maximum | 105 mm; range is reader dependent: observe http://support.automation.siemens.com/WW/view/en/67384964 | |
| protocol / with radio transmission | RF300-specific | |
| transfer rate / with radio transmission / maximum | 106 kbit/s | |
| product feature / multitag-capable | Yes | |
| electrical data | | |
| product component / backup battery | No | |
| memory | | |
| type of memory | FRAM / EEPROM | |
| storage capacity / of the user memory | 8189 byte | |
| type of memory organization | UID (fixed code) 4 bytes, user memory 8189 bytes, OTP memory 20 bytes | |
| number of read cycles / at ambient temperature < 40 °C / maximum | 1000000000 | |
| number of write cycles / at ambient temperature < 40 °C / maximum | 1000000000 | |
| data retention time / at ambient temperature < 40 °C / not less than | 10 y | |
| property of memory | Block-by-block write protection of the OTP memory | |
| mechanical data | | |
| material | PA12 | |
| color | anthracite | |
| mounting distance / relating to metal surfaces / recommended / minimum | 0 mm | |
| ambient conditions | | |
| ambient temperature | | |
| during read/write access | -25 +85 °C | |
| outside the read/write area | -40 +85 °C | |
| during storage | -40 +85 °C | |
| protection class IP | IP67/IPx9K | |
| shock resistance | According to DIN EN 60721-3-7 Class 7 M3 | |
| shock acceleration | 500 m/s ² | |
| vibrational acceleration | 200 m/s² | |
| design, dimensions and weights | | |
| width | 25 mm | |
| height | 15 mm | |

| depth | 48 mm |
|---|---|
| net weight | 25 g |
| fastening method | 2 x M3 screws |
| product features, product functions, product components / general | |
| product feature | |
| • silicon-free | Yes |
| • printable | No |
| standards, specifications, approvals | |
| certificate of suitability | |
| • IECEx | No |
| MTBF | 1200 y |
| further information / internet-Links | |
| Internet-Link | |
| to web page: selection aid TIA Selection Tool | https://support.industry.siemens.com/cs/ww/en/view/67384964 |
| to website: Industrial communication | http://www.siemens.com/ident/rfid |
| • to website: Industry Mall | https://mall.industry.siemens.com |
| to website: Information and Download Center | http://www.siemens.com/industry/infocenter |
| to website: Image database | http://automation.siemens.com/bilddb |
| to website: CAx-Download-Manager | http://www.siemens.com/cax |
| to website: Industry Online Support | https://support.industry.siemens.com |
| | |

last modified: 6/1/2021 🖸