

DINO-LITE AM4115ZTL



The wide range of magnification (10-140x), the large field of view and working distance of up to 23 cm makes the AM4115ZTL the ideal solution for all situations where a longer distance between the microscope and the object is required or when it is needed to work under the microscope (repair, rework and assembly tasks etc.)

The built-in adjustable polarizer reduces glare and reflection on shiny objects.

| Model | AM4115ZTL |
|-----------------------|---|
| Resolution | 1,3 megapixel (1280x1024 pixels) |
| Magnification | 10-140x |
| Interface | USB 2.0, High speed USB transmission |
| Nr. of LED's | 8 |
| LED on/off switchable | Yes |
| LED color | White |
| Housing | Composite/ plastic housing |
| Microtouch | Yes |
| Magnification lock | Yes |
| ESD safe | No |
| Output | Picture, video |
| Video Frame Rate | up to 30 frames-per-second |
| Measurement | Yes (line, radius, circle, 3-point circle, etc.) |
| Calibration | Yes |
| Filter/Diffuser | IR cut-filter >650 nm / Diffuser N3C-D included |
| Compatibility | Windows XP, Vista, 7, 8 & 10, MacOS 10.9 and up |
| Software (Included) | Windows: DinoCapture 2.0, Mac: DinoXcope |
| Package contents | Microscope, Carry pouch, Software CD, Calibration target, User manual, N3C-O- Open cap, N3C-C- Closed cap, N3C-D-Diffuser cap, N3C-Extension cap, N3C-L- Long cap, N3C-S-Side light cap |
| | |