

VOLTCRAFT - TOP PERFORMANCE IN EVERY WAY

For more than 40 years, our product range has been dynamically adapting to the constant changes in the industry. We commit to offering first-class quality to our customers while delivering an excellent cost-performance ratio. This philosophy remains the cornerstone of Voltcraft's success.

DSP-6010 Laboratory power supply

CE

Item no: 2446087

The power supply is used as a potential-free DC mains supply to operate low-voltage devices. It is connected via 4 mm safety sockets. The output voltage and current can be adjusted. The DC output is electrically isolated and features protective isolation towards the mains voltage.



FEATURES

Colour LCD display // 1-channel output // Low ripple/noise // Over voltage/Over current protection // USB 2.0 interface

TECHNICAL DATA

Input

Item	Value
Supply Voltage	200 - 240 V/AC
Input Frequency	50/60 Hz
Input active power	300 W
Input maximum apparent power	max. 800 VA
Full Load Input Current	≤2.8 A
No-Load Input Current	≤150 mA
Input Fuse	250V, F5A

Output

Item	Value
Voltage	0 - 60 V
Current	0 - 10 A
Max output power	300 W
Efficiency (rated load)	85 %

Regulation (CV)

Item	Value
Load	≤30 mV
Line	≤20 mV

Regulation (CC)

Item	Value
Load	≤30 mV
Line	≤20 mV

Ripple and Noise

Item	Value
Voltage (Vp-p)	≤50 mV
Voltage (rms)	≤5 mV
Current (Ap-p)	≤30 mA

Setting Resolution

Item	Value
Voltage	10 mV
Current	1 mA

Readback Resolution

Item	Value
Voltage	10 mV
Current	1 mA

Setting Accuracy

Item	Value
Voltage	≤0.1 % ± 30 mV
Current	≤0.1 % ± 10 mA

Readback Accuracy

Item	Value
Voltage	≤0.1 % ± 30 mV
Current	≤0.1 % ± 10 mA

Response time

Item	Value
Transient recovery time (50 - 100 % rated load)	≤1 ms

Protective function

Item	Value
OVP	0 - 61 V
OCP	0 - 10.1 A
OTP	85 °C

Temperature coefficient (output)

Item	Value
Voltage	100 ppm/°C
Current	200 ppm/°C

Temperature coefficient (readback)

Item	Value
Voltage	100 ppm/°C
Current	200 ppm/°C

Display

Item	Value
Display Type	7.1 cm (2.8") colour LCD
Resolution	240 x 320 pixels
Colour	65536 colour, TFT

Environment

Item	Value
Working temperature	0 to +40 °C
Storage temperature	-20 to +60 °C
Relative Humidity	≤90 % RH (non-condensing)
Altitude	2,000 m
Cooling	Fan cooling, temperature intelligent speed control

Others

Item	Value
Communication Port	USB communication, compatible with SCPI communication protocol
USB Charging Port	5 V/DC, 1 A
Dimension (W x H x D)	226 x 142 x 82 mm
Weight (approx.)	1.5 kg

CONTENTS

Power supply // Mains cable // USB cable // Fuse // CD ROM // Safety instructions // Operating instructions

This is a publication by Conrad Electronic SE, Klaus-Conrad-Str. 1, D-92240 Hirschau (www.conrad.com).

All rights including translation reserved. Reproduction by any method (e.g. photocopying, microfilming or the capture in electronic data processing systems) requires prior written approval from the editor. Reprinting, also in part, is prohibited. This publication reflects the technical status at the time of printing.

Copyright by Conrad Electronic SE.

*2446087_V1_0323_en_ds 809416203 11/01 en