

Cable Harnessing Accessories

Polyester Braided Sleeving

multicomp PRO



Features

- High expansion
- Reduces inventory
- Easy installation over wire bundles
- Ideal for large termination or cable transitions
- High abrasion and good chemical resistance
- Available in black
- Self extinguishing due to its braided construction
- Supplied on coils
- Expandable braided sleeving is made of polyester monofilaments. Its specially designed construction provides a high expansion ratio of 1:3 which enables a very easy and quick fitting over bundles of cables. Due to its high expansion, only few references are necessary, which allow you to cover a wide range of diameters
- With a continuous working temperature of -50°C to +150°C and a resistance to most chemicals, it can be used in hostile conditions and is suitable for all industrial processes

Specifications

Monofilament	: Polyester - size 0.22 mm
Melting Point	: +250°C
Limiting Oxygen Index	: 33% (CEI 684-2)
Working Temperature	: -50°C to +150°C
Withstand Peaks	: 220°C
Flame Resistance	: Passes flame resistant requirements of CEI 332-1 and FMVSS 302 (Type A) I2 according to NF F16-101
Fume Toxicity	: Passes CEI 754-1 and CEI 754-2 Halogen free
Fumes Opacity	: Passes NF C 20452 (polymer)
Chemical Resistance	: Unaffected by most chemicals

Specification Table

Nominal Diameter	Range of Use Advise		Coil Length (m)	Number of Yarns	Weight Gr / m	Part Number
	Minimum	Maximum				
6	4	12	100	48	2.8	PETL-6-BK 100C
12	7	21	100	144	8	PETL-12-BK100C
20	10	30	100	216	12	PETL-20-BK100C
30	20	60	50	288	16.5	PETL-30-BK50C

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp PRO