## NC machine reamer HSSE with uniform shank (diameter can be selected)

for universal use up to 1000 N/mm<sup>2</sup>



## Application



Version

■ 7-8° left-hand spiral, type B

## Advantage

- Delivered ex stock
- high-quality HSSE cutting material for a very long service life
- good bore hole quality (dimensional tolerance, roundness, surface quality)

	Application	plication Steel (N/mm²)			Stainless steel		Alu		Brass				Plas-	Graphite	GG(G)	Titan-	Nickel-		Hard mat.	
		<700	<1000	<1300	marten.	austen.	short	long	short	long	short	long	tics	G(C)FK	GjMW	alloy	alloy	alloy	<55 HRC	<65 HRC
Ī		12	9	7	8	7	17	17	17	17	13	13			11	5	5			

Art. No.	11625 512					
Cutting material	HSSE					
Tolerance of fit	0 / +0,004 mm					
Groove type	Left-hand twist, 7-8°					
Tool holding device	HA parallel shank					
Min./max. cutting edge diameter	1.71-1.9 mm					
Length	46 mm					
Cutting edge length	10 mm					
Projecting length	20 mm					
Shaft diameter	2 mm					
Number of cutting edges	4 PCS					
f steel 1300	0.12 mm/r					
DIN	Similar to 212					

## **EAN-Code**

4050293430691

