

RoHS
Compliant



Features

- Overload protection and over-voltage protection.
- Over temperature protection with auto-recovery.
- Compliant with QC4+, CE, FCC standards.
- Specially designed for your Type-C supported devices.

Part Number Table

Description	Part Number
Sealed Slide Switch, 4PDT, Through Hole, 300mA, 125V	SPC21205

Mechanical	
Colour	Black
Size	Main body: 62mm × 63.4mm × 30mm (L×W×H) (UK)
Environmental	
Operating Temperature Range	0 ~ 35°C
Storage Temperature Range	-20°C ~ +85°C
Operating Relative Humidity	20% ~ 90% RH
Storage Relative Humidity	5% ~ 95% RH
Certification	CE, FCC
User Manual	English Version
Input/output	
Input	100-240V AC 50/60Hz
Output	PD3.0: 5V/3A, 9V/3A, 12V/2.25A QC4.0: 3.3~5.9V/3A, 3~11V/2.45A
Input Socket	UK plug
Protection	
Over Current	Yes
Short Circuit	Yes
Over Temperature Protection	Yes
Over Voltage Protection	Yes
Performance	
Ripple And Noise	5V: ≤150mV 9V/12V: ≤200mV
Turn on Delay Time	3s max.
Rise time	20mS
Line Regulation	±3%
Efficiency	3V: ≥79.7% 5V: ≥81.4% 9V: ≥86.7% 12V: ≥86.7%

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.