



EU type-examination certificate

according to Article 19 (c) of Regulation (EU) 2016/425 of the European Parliament and of the Council

No.: 1019-504/Q/2019

Manufacturer:	Honeywell Fall Protection SAS, 35 – 37, Rue de la Bidauderie, 18100 Vierzon, France
Product:	RG500 Auto/Manual Rope Grab, type Guided type fall arresters including a flexible anchor line 1035951, 1035950, 1035949, der. variations 1035939, 1035940, 1035941, 1035942, 1035943, 1035944, 1035945, 1035946, 1035947, 1035948
PPE category:	III.
Applied standards and/or technical specification:	ČSN EN 353-2:2003 (identical to EN 353-2:2002) ČSN EN 795:2013 (identical to EN 795:2012) ČSN EN 12841:2007 (identical to EN 12841:2006) ČSN EN 365:2005 (identical to EN 365:2004) Technical specification No. 37378-FP-RG500/2019, dated February 27, 2019
Base for issue of certificate:	Evaluation report No. 1019-019409/2019 (integral part of this certificate)
Conditions of validity:	Certificate shall only be used in conjunction with one of the conformity assessment procedures referred to Article 19 (c) point i) or ii) of Regulation (EU) 2016/425 of the European Parliament and of the Council.
Validity of certificate till:	2024-11-26

VVUÚ, a.s. hereby certifies that the sample of the product mentioned above meets all the relevant essential health and safety requirements of Annex II of the Regulation (EU) 2016/425 of the European Parliament and of the Council.



2019-11-27
Date of issue

Ing. Tomáš Dorazil
Deputy Director NB 1019

Description of product

Guided type fall arrester including a flexible anchor line (EN 353-2:2002) + Type A rope adjustment devices (EN 12841:2006)

Guided type fall arrester:	Stainless steel SS304, 1.4301 (X5CrNi18-10)
Lanyard:	Type 1035951 – without connector Type 1035950 – PES/VECTTRAN webbing, width 25,5 mm with two sewing eyes and connector, length 0,3 m Type 1035949 - PES/VECTTRAN webbing, width 25,5 mm with two sewing eyes and connector, length 1,0 m
Anchor line:	Low stretched kernmantel rope of diameter of 12 mm, material PES/ PA
Anchor line – length:	5 – 50 m
Max. loading:	140 kg
Trademark:	Honeywell MILLER®

Anchor devices (EN 795:2012, type B)

Material	Stainless steel SS304, 1.4301 (X5CrNi18-10)
Strength:	18 kN
Anchor device:	Type B acc. to EN 795:2012, intended for using by only one person
Using:	The product must not be used separately for arrestment of user's free fall.
Trademark:	Honeywell MILLER®

Picture of product



RG500 Auto/Manual Rope Grab,
 type Guided type fall arresters
 including a flexible anchor line
 1035951



RG500 Auto/Manual Rope Grab,
 type Guided type fall arresters
 including a flexible anchor line
 1035950



RG500 Auto/Manual Rope Grab,
 type Guided type fall arresters
 including a flexible anchor line
 1035949