

DET14C and DET24C

Clamp-on Ground Resistance Testers



- **Large elliptical clamp design**
- **Smooth mating surfaces on the clamp head**
- **CATIV 600 V operation**
- **Noise filter function**
- **Intelligent data hold function**
- **Data storage with time- and date-stamped results**

DESCRIPTION

The DET14C and DET24C are advanced clamp-on ground resistance testers that set new standards in terms of access, performance, features, simplicity of operation and safety. The DET14C and 24C are used to measure earth/ground resistance in multiple loop installations without disconnecting the ground.

Designed with flat core ends, these units prevent dirt build-up, ensuring measurement integrity and improved reliability over products with interlocking teeth. Other enhancements include safety to CATIV 600V, a built-in filter function for electrically noisy environments, time and date stamped stored test results and ultra long battery life. Megger has taken what is now a standard test method and significantly improved its field applicability.

The DET14C and DET24C are designed to quickly measure ground electrode resistance in applications where this type of test method can be used and/or verify the integrity of ground connections. The goal of ground resistance testing is to ensure that the resistance ground electrode system is low enough to prevent or limit voltage rises caused by fault current, electrical surges, lightning strikes, etc.

Clamp-on ground testers work in applications where there is a loop resistance to measure with ground paths in the system (the more ground paths, the closer to the actual resistance). A utility pole ground system is a classic example of this type of application.

Typical end users include:

- Power utilities
- Electrical contractors/electricians
- Specialist grounding contractors
- Electrical testing companies
- Telecommunications companies
- Railroads
- Mining companies



The DET14C is being used to test a pole ground.



The DET14C is shown measuring a ground spike in a ground well.

APPLICATIONS

Typical testing applications include:

- Pole grounds
- Service entrance/meter ground electrodes
- Service panels
- Pad mount transformer grounds
- Transmission tower grounds - utility ground cables
- Telephone pedestals
- Telephone cabinets
- Lightning protection ground electrodes

FEATURES AND BENEFITS

Large elliptical clamp (head) design

- Allows testing of round cables/rods up to 37 mm diameter and ground tapes/straps up to 50 mm width
- Improved testing access

Smooth mating surfaces on the clamp head

- Easy to clean
- No interlocking teeth to damage

CATIV 600 V operation

- Highest level of user safety available
- Unit can be used safely before the distribution board

Noise filter function

- User can select the filter function to increase noise immunity
- Allows the unit to be used in higher electrical noise environments

Resistance and current limit alarm functions (visual and audible)

- Minimum and maximum limits can be set to reduce test time/improve accuracy

Intelligent data hold function (preset before testing)

- Increases instrument ease of use in difficult testing locations

Backlit display

- Allows for operation in low light environments such as cable basements

Data storage (both models)/results downloading (DET24C)

- Reduces potential for error in recording results

Time and date stamped results

- Improved data/results management
- Improved accuracy of result reporting

New ergonomic trigger design

- Easier and more comfortable to operate
- Less chance of slippage causing the head to snap shut

Ultra long battery life (24 hours continuous) with readily available batteries

- Longer operating time
- Reduced cost of ownership

ELECTRICAL SPECIFICATIONS

Resistance Measurements

Ground Resistance Range	Resolution	Accuracy
0.05 Ω to 0.99 Ω	0.01 Ω	± 1.5% ± 0.05 Ω
1.00 Ω to 9.99 Ω	0.01 Ω	± 1.5% ± 0.1 Ω
10.0 Ω to 99.9 Ω	0.1 Ω	± 2% ± 0.5 Ω
100.0 Ω to 199.9 Ω	0.1 Ω	± 5% ± 1 Ω
200 Ω to 400 Ω	1 Ω	± 10% ± 10 Ω
400 Ω to 600 Ω	1 Ω	± 10% ± 10 Ω
600 Ω to 1200 Ω	10 Ω	± 20%
1200 Ω to 1500 Ω	10 Ω	± 35%

- Frequency of measurement 1390 Hz.

Alarm Settings

Alarm Type	Range	Resolution
Threshold 1	1 - 1500 Ω	1 Ω
Threshold 2	0 - 1500 Ω	1 Ω

Current Measurement (RMS)

Current Range	Resolution	Accuracy
0.5 mA to 0.99 mA	0.01 mA	± 2% ± 0.05 mA
1.00 mA to 9.99 mA	0.01 mA	± 2% ± 0.05 mA
10.0 mA to 99.9 mA	0.1 mA	± 2% ± 0.1 mA
100 mA to 999 mA	1 mA	± 2% ± 1 mA
1.00 A to 9.99 A	0.01 A	± 2% ± 0.01 A
10.0 A to 35.0 A	0.1 A	± 2% ± 0.1 A

- True RMS readings up to a crest factor of 5.0 (peak current 40 A)
- Accuracy guaranteed for 50 Hz and 60 Hz
- Measurement over the range 16 Hz to 400 Hz
- Maximum current is 100 A RMS continuous and 200 A RMS for 60 s max at 50 Hz and 60 Hz

GENERAL SPECIFICATIONS

Maximum jaw opening	39 mm
Maximum jaw inner dimensions	39 mm x 55 mm
Display type	4 + 6 digit with backlight
Battery type	4 x 1.5 V IEC LR6/AA alkaline
Battery life	24 hours continuous testing – while measuring a 25 Ω resistance without backlight
Auto power down button	300 s (reset by jaw action or button press)
Data logging	DET14C 256 records DET24C 2,000 records
Data download	Opto-coupled IrDA-USB interface (DET24C only)
Range selection	Automatic within each mode
Sample time	< 1 s
Hold function	Yes with visual indicator
Alarm function	Yes with visual indicator
Noise filter function	Yes, automatic
Warning buzzer	Yes
Operating temperature, humidity	-4 °F to +122 °F, <85% RH (-20 °C to +50 °C)
Storage temperature, humidity	-40°F to +140 °F, <75% RH (-40 °C to +60 °C)
Weight	2.17 lb (985 g)
Instrument dimensions LxWxH	9.7 in. x 4.4 in. x 2 in. (248 mm x 114 mm x 49 mm)
IP rating	IP30 with jaws closed
Performance	IEC 61557-5 IEC 61557-13 Class 1
Safety	EN 61010-2-032 CATIV 600V Pollution degree 2
EMC	Class B Compliant, IEC 61326, BSEN 61326




The clamp head of the DET14C/24C has a smooth mating surface and no interlocking teeth. Its large elliptical design improves access to the test specimen.



Close up of instrument's front panel.

DET14C/24C DISPLAY VIEW

	Save		Tick = set
	Open		Cross = not set
	Delete		Warning refer to user guide
	IrDA download		Signal noise detected
	Alarm		Less than
	Filter		More than
	Battery		
HOLD	Hold		
D:M:Y			
M:D:Y	Date formats		
H:M:S	Hours, minutes, seconds		
	Clamp open		



DET24C INSTRUMENT FRONT VIEW



Both units come with a carrying case, carrying strap, batteries, calibration check, and user guide CD.

DET24C also includes USB IrDA dongle and PowerDB Lite software.

ORDERING INFORMATION

Item (Qty)	Cat. No.
DET14C Digital earth test clamp-on meter	1000-761
DET24C Digital earth test clamp-on meter	1000-762
Included accessories	
Carrying case	1001-715
Carrying strap (wrist loop)	1001-716
User guide CD-ROM	1001-198
Calibration check	1001-498
Battery AA (Alkaline) (4 required)	25511-841
Included accessories for DET24C only	
USB IrDA dongle	90001-434
PowerDB Lite software	1000-576

UK
Archcliffe Road, Dover
CT17 9EN England
T +44 (0) 1 304 502101
F +44 (0) 1 304 207342
UKsales@megger.com

UNITED STATES
4271 Bronze Way
Dallas, TX 75237-1019 USA
T 1 800 723 2861 (USA only)
T +1 214 333 3201
F +1 214 331 7399
USsales@megger.com

OTHER TECHNICAL SALES OFFICES
Valley Forge USA, College Station
USA, Sydney AUSTRALIA, Täby
SWEDEN, Ontario CANADA, Trappes
FRANCE, Oberursel GERMANY, Aargau
SWITZERLAND, Kingdom of BAHRAIN,
Mumbai INDIA, Johannesburg SOUTH
AFRICA, and Chonburi THAILAND

ISO STATEMENT
Registered to ISO 9001:1994 Reg no. Q 09250
Registered to ISO 14001 Reg no. EMS 61597

DET14C_24C_DS_US_V02
www.megger.com
Megger is a registered trademark